



032U453416

Solenoid valve, EV220B, Function: NC, G, 1, 11 m³/h, NBR

This product has been discontinued.

018F7358

132U2500

032U7126

042N1256

Media recommendations: Water,Brine,Oil,Air, Approval: DNVGL-CG-0339; CE, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

PRODUCT DETAILS

Gross weight	1.654 Kilogram
Net weight	1.592 Kilogram
Volume	1.295 Liter
EAN	5702423187126
Type	EV220B
Product group	Solenoid valves
Product Name Description	Solenoid valve
Actuator	B
Actuator size	13.5 mm
Actuator size [in]	0.53 in
Actuator system [mm]	13.5 mm
Ambient temperature max. [°C]	80 °C
Ambient temperature max. [°F]	176 °F
Application	Open
Approval	CE DNVGL-CG-0339
Body material	Brass
CE mark	Yes
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.3
Coil option	Clip-on
Coil type	BB
Connection Internal/External	Internal
Connection material	Brass
Connection size [in]	1
Connection standard	ISO 228-1
Connection type	G
Contains batteries	No
Cv value [gal/min]	12.7 gal/min
Differential pressure [bar] [max]	16 bar
Differential pressure [bar] [min]	0.3 bar
Differential pressure [psi] [max]	232 psi
Differential pressure [psi] [min]	4.35 psi
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical connection	Spade DIN 43650-A
Enclosure rating IP	IP65

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Est. time to open, water [ms]	300 ms
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flow direction	Single-flow
Flow direction indicator	Embossed 1-way arrow
Fluid Group	1
Frequency [Hz]	50 Hz
Function	NC
In scope of WEEE	Yes
Kv value [m³/h]	11 m ³ /h
Max media viscosity [cSt]	50 cSt
Max. test pressure [bar]	24 bar
Max. test pressure [psig]	348 psig
Max. Working Pressure [bar]	16 bar
Max. Working Pressure [psig]	232 psig
Media recommendations	Water,Brine,Oil,Air
Media tolerance comments	Neutral media
Medium temperature range [°C] [max]	90 °C
Medium temperature range [°C] [min]	-10 °C
Medium temperature range [°F] [max]	194 °F
Medium temperature range [°F] [min]	14 °F
Number of ways	2/2
Open/close equalizing orifice	Optional Equalization orifice
Operation	Servo-operated (diaphragm)
Orifice size [mm]	25 mm
Orifice size fraction [in]	1 in
Packing format	Multi pack
Parts Program name	EV220B 15 - 50
Power consumption [W] 50Hz	11 W
Product accessories	Solenoid coil accessories Solenoid valve accessories
Quantity per packing format	12 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
SCIP dossier no.	b8af40bc-3f7f-4177-bd55- c3503cccfc04
SCIP dossier product name	EV220B 15-50 brass NC - solenoid valve
Seal Material	NBR
Serviceable	Solenoid valve spare parts
Specification key	EV220B 25B G 1N NC000 BB024AS
Supply voltage 50Hz Max [V]	24 V
Supply voltage [V] AC	24 V
Type designation	EV220B 25

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.