

# ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/gb/products/2907518>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



ECOR-1... relay base, for miniature power relay or miniature switching relay with 1 or 2 changeover contacts, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

## Commercial data

Item number	2907518
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	DKF312
Product key	DKF312
GTIN	4055626214351
Weight per piece (including packing)	49.44 g
Weight per piece (excluding packing)	50.86 g
Customs tariff number	85366990
Country of origin	CN

# ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/gb/products/2907518>

## Technical data

### Product properties

Product family	ESSENTIAL edition
----------------	-------------------

### Electrical properties

Nominal voltage $U_N$	250 V AC/DC
Nominal current $I_N$	12 A

### Connection data

#### Input side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross-section flexible	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)

#### Output side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross-section flexible	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)

### Dimensions

Width	15.7 mm
Height	79.2 mm
Depth Retaining bracket	69 mm (ECOR-RH-1L) 78 mm (ECOR-RH-1H)

### Material specifications

Color	traffic gray B (RAL 7043)
-------	---------------------------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

### Mounting

# ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/gb/products/2907518>

Mounting type	DIN rail mounting
Mounting position	any

# ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/gb/products/2907518>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/2907518>



**cUL Recognized**  
Approval ID: FILE E 113228



**UL Recognized**  
Approval ID: FILE E 113228



**EAC**  
Approval ID: RU C-DE.\*\*08.B.01419



**cULus Recognized**  
Approval ID: E113228

# ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/gb/products/2907518>

## Classifications

### ECLASS

ECLASS-13.0	27371603
ECLASS-15.0	27371603

### ETIM

ETIM 9.0	EC001456
----------	----------

### UNSPSC

UNSPSC 21.0	39122300
-------------	----------

# ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/gb/products/2907518>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

### EF3.1 Climate Change

CO2e kg	0.869 kg CO2e
---------	---------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)