



IEC guide frame, frame size 2; rated current 2000A AC; breaking capacity S, M, H; 3-pole; connection horizontal, with two-piece shutter, interlockable any circuit breaker or non automatic circuit breaker with COM w/o position signaling switch PSS .

Model	
product brand name	SENTRON
size of the circuit-breaker	2
number of poles	3
design of the product	AC
type of electrical connection	suitable for circuit breakers: 2000 A
type of electrical connection / for main current circuit	rear horizontal
pack type	standard packaging
Weight	47.775 kg
Net Weight	32.775 kg

Approvals / Certificates

General Product Approval	EMV	Test Certificates
--------------------------	-----	-------------------

[Confirmation](#)



[Miscellaneous](#)

Maritime application	other
----------------------	-------



[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=3WA8220-5AA32-1BA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA8220-5AA32-1BA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=3WA8220-5AA32-1BA1

CAX-Online-Generator

<https://www.siemens.com/cax>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

11/24/2025

