



## PRODUCT-DETAILS

**A2N 250 TMF 250-2500 3p F F****A2N 250 TMF 250-2500 3p F F****General Information**

<b>Extended Product Type:</b>	A2N 250 TMF 250-2500 3p F F
<b>Product ID:</b>	1SDA066786R1
<b>EAN:</b>	8015644006969
<b>Catalog Description:</b>	A2N 250 TMF 250-2500 3p F F
<b>Long Description:</b>	C.BREAKER FORMULA A2N 250 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 250-2500 A
<b>Display Name:</b>	A2N 250 TMF 250-2500 3p F F

**Material Compliance**

<b>REACH Declaration:</b>	9AKK108466A1425
<b>RoHS Declaration:</b>	9AKK108466A1424
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108467A5658
<b>Toxic Substances Control Act - TSCA:</b>	9AKK108467A8326
<b>SCIP:</b>	d1929411-2550-45c3-981d-8e32a25cda10 Italy

<b>Simplified SCIP:</b>	af4e9876-3b45-4ea9-b933-16e5843fe0e7 Germany 037c8cff-3898-48cb-a00b-56f2f29acc4a Sweden dfe59f06-471c-48d1-8df0-de14b7970792 Poland 9a350c64-5162-4460-9b1d-1ccf992d214f Poland f2bbeb6d-fc7a-4fd9-bd32-b59724d5602b Hungary c0015ae7-e30d-46c6-a918-8c560661e0f4 Estonia dda9a866-a6e4-436d-a345-17a0f14c2f25 Greece f3147701-7912-4b10-82da-68ea6af4217f Spain 57a01a2e-9cf5-4a6e-b616-524f75bac232 Netherlands f319f9c9-83d8-4860-812e-6b3cd6cf28ad Belgium 02e82c4e-c3be-4c94-814d-ac1663d608d0 Czech Republic b338be39-4200-4caa-8ec7-75c7ac95c1c7 Belgium a43d42d9-7f40-45b5-be88-6c4753a85abe Germany 1505cc81-948c-47f9-8878-be22764a816b Germany 85fc4881-27b7-43da-9ef6-db4c3e74ead9 Sweden c5c9acf8-e5b1-4df5-9afe-fc796bac6a42 Poland 54f31efe-eb64-449e-a291-bd9408b1ef55 France f17031ce-bfff-4a0a-b2a5-eb732d64de5a Finland 85200cd0-ace4-462a-9379-3ddb92474764 Norway 2d175bf1-61d0-4664-82f7-8a48d2d57245 Croatia 523e9a5b-5ff0-4808-b187-d1b2622e92b0 Germany c0e90066-dad5-4236-8fdb-82aa32dcaad0 Germany 874e8f62-e18e-41ab-80c1-ea7a87411216 Hungary 7b84413c-aaab-4166-98e2-e1f959ad7b3d France 2e43f0a8-e4f2-45f0-950d-174515d50d01 Denmark d237d040-c047-4173-899c-73b34db6317e Portugal 9eec0e91-c647-42b8-92f6-7c6b7f651075 Bulgaria
-------------------------	--

---

## Environmental

<b>Environmental Information:</b>	1SDL000183R0001 9AKK108467A6707
-----------------------------------	------------------------------------

---

## Ordering

<b>Order Code US and Canada:</b>	ABN250TW
<b>EAN:</b>	8015644006969
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85362090

---

## Dimensions

<b>Product Net Width:</b>	105 mm
<b>Product Net Height:</b>	150 mm
<b>Product Net Depth / Length:</b>	60 mm
<b>Product Net Weight:</b>	1.394 kg

---

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	162 mm
<b>Package Level 1 Height:</b>	120 mm

Package Level 1 Depth / Length:	155 mm
Package Level 1 Gross Weight:	1.467 kg
Package Level 1 EAN:	8015644006969

## Additional Information

Product Main Type:	SACE FORMULA
Product Name:	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker
Version:	F

## Technical

Electrical Durability:	4000 cycle
Mechanical Durability:	10000 cycle
Number of Poles:	3P
Opening Time:	CB with SOR 15 ms CB with UVR 15 ms
Power Loss:	at Rated Operating Conditions per Pole 16 W
Rated Current ( $I_n$ ):	Main Circuit 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	6 kV
Rated Insulation Voltage ( $U_i$ ):	690 V
Rated Operational Voltage:	550 V AC 250 V DC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(240 V AC) 42.5 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 12.5 kA (480 V AC) 12.5 kA (500 V AC) 5 kA (250 V DC) 2 Poles in Series 18 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(240 V AC) 85 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 25 kA (480 V AC) 25 kA (500 V AC) 10 kA (250 V DC) 2 Poles in Series 36 kA
Rated Uninterrupted Current ( $I_u$ ):	250 A
Release:	TMF
Release Type:	TM
Short-Circuit Performance Level:	N
Standards:	IEC
Sub-type:	A2
Terminal Connection Type:	Front

## Certificates and Declarations

<b>Data Sheet, Technical Information:</b>	1SDC210032D0204
<b>Declaration of Conformity - CE:</b>	9AKK106713A5518
<b>Wiring Diagram:</b>	1SDM000067R0001
<b>Instructions and Manuals:</b>	1SDH000718R0001

---

## External Classifications and Standards

---

<b>ETIM 9:</b>	EC000228 - Power circuit-breaker for trafo/generator/installation protection
<b>ETIM 10:</b>	EC000228 - Power circuit-breaker for trafo/generator/installation protection
<b>Object Classification Code:</b>	Q
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)
<b>eClass:</b>	V11.1 : 27370409

---

---

## Categories

---

Products > Low Voltage Products and Systems > Circuit Breakers > Moulded Case Circuit Breakers > Formula DSA

