

draw-out molded case circuit breaker without guide frame frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 3-pole ETU350, LSI, In=1600A rotary coding switch Ir=640...1600A Isd=1...10xIn, li=1.5...15xIn N conductor protec. adjustable opt. w. ext. CT; up to 200% main contacts f. draw-out vers. No communication connection, no measurement function Motorized operating mechanism 220...250 V AC/DC incl. S21 spring energy store signaling switch With electr. and mech. calling Switch-on solenoid (CC) 220-240 V AC/DC with 2nd auxiliary release UVR time-del Undervoltage 220-240 V AC/DC incl. ext. time-delay device With 1st auxiliary release, ST Shunt release 220-240 V AC/DC

Model	
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	spring actuator
type of the driving mechanism	motor drive
type of the driving mechanism / motor drive	Yes
design of the overcurrent release	ETU350
General technical data	
number of poles	3
mechanical service life (operating cycles) / typical	10 000
electrical endurance (operating cycles) / at AC-1 / at 380/415 V	2 000
insulation voltage / rated value	1 000 V
continuous current / rated value / maximum	1 600 A
Supply voltage	
operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
Protection class	
protection class IP / on the front	IP20
Breaking Capacity	
switching capacity class of the circuit breaker	M
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	141 W
• maximum	423 W
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the short-time delayed short-circuit release	
• initial value	1 600 A
• full-scale value	16 000 A
adjustable current response value current / of the current-dependent overload release / initial value	640 A
Product details	
product component	
• trip indicator	Yes
• voltage trigger	Yes
• undervoltage release	Yes
Product function	
product function	
• grounding protection	No
• communication function	No
Display and operation	

<b>display version</b>	Without display
<b>Short circuit</b>	
<b>operating short-circuit current breaking capacity (Ics)</b>	
• at 240 V / rated value	100 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	55 kA
• at 500 V / rated value	36 kA
• at 690 V / rated value	25 kA
<b>maximum short-circuit current breaking capacity (Icu)</b>	
• at 240 V / rated value	100 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	55 kA
• at 500 V / rated value	36 kA
• at 690 V / rated value	25 kA
<b>short-circuit current making capacity (Icm)</b>	
• at 240 V / rated value	220 kA
• at 415 V / rated value	121 kA
• at 440 V / rated value	121 kA
• at 500 V / rated value	75.6 kA
• at 690 V / rated value	53 kA
<b>Connections</b>	
arrangement of electrical connectors / for main current circuit	rear side
type of electrical connection / for main current circuit	contact knife
<b>Mechanical Design</b>	
<b>height</b>	364 mm
<b>width</b>	278 mm
<b>depth</b>	271 mm
<b>fastening method</b>	drawer unit
<b>Net Weight</b>	14.92 kg
<b>Environmental conditions</b>	
<b>ambient temperature / during operation</b>	
• minimum	-25 °C
• maximum	70 °C
<b>ambient temperature / during storage</b>	
• minimum	-40 °C
• maximum	70 °C

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2716-1AC30-4HP7>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2716-1AC30-4HP7>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2716-1AC30-4HP7](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2716-1AC30-4HP7)

##### CAX-Online-Generator

<https://www.siemens.com/cax>

##### Tender specifications

<https://www.siemens.com/specifications>

##### Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



---

last modified:

11/24/2025 

