



E2E-X4B1TL12-M1TJ 0.3M

Proximity sensor, inductive, nickel-brass, long body, M12, shielded, 4 mm, DC, 3-wire, PNP NO, IO-Link COM3, M12 pigtail
Smartclick connector, 0.3 m

Specifications

Size	M12
Mounting type	Quasi-flush
Sensing distance	4 mm
Overall length of sensor	69.1 mm
Thread length	55 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	M12 pigtail Smartclick connector
Cable specifications	PVC (oil-resistant)
Cable length	0.3 m
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

Related products



M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

CAD Library



E2E NEXT Datasheet

EN PDF 40 MB



E2E(Q) - Basic Models Index list

EN PDF 7.27 MB



E2E(Q) - Premium Models Index list

EN PDF 719 KB



E2E(Q)- XB_XC_basic_model Instruction Sheet

EN PDF 2.28 MB



E2E[Q]-XxBxxxx IO-Link IODD file

EN ZIP 1.35 MB



E2E_Q DC 3-wire Eu declaration of conformity

EN PDF 130 KB



IO-Link Series Brochure

EN PDF 7.95 MB