



CP-8050 Master Module coated circuit board.

Figure similar

General technical data	
consumed active power / rated value / maximum	4 500 mW
surge voltage / rated value	4 kV
surge voltage resistance	2.5 kV
processor clock frequency	800 MHz
product feature / redundancy capability through firmware expansion	Yes
storage capacity / of the RAM	512 Mbyte
storage capacity / of the flash memory	4 Gbyte
product component / hardware real time clock	Yes
accuracy [ppm] / of the hardware real time clock	5 ppm
buffer time / of the hardware real time clock / in case of power failure	72 h
Product details	
time resolution	1 ms
number of local IO modules / maximum	128
number of allowable IO lines / maximum	16
number of data points / maximum	400 000
Measuring functions	
sampling interval	10 ms
Supply voltage	
type of voltage / of the supply voltage	DC
Inputs / Outputs	
number of digital inputs	0
number of isolated output groups	1
number of digital outputs	2
design of the digital output	relais
type of voltage / at digital output	DC
voltage / at DC / per output	24 ... 60 V
voltage / per output	18 ... 70 V
consumed current / per output	1 000 mA
switching capacity apparent power / at AC / at 50 Hz	30 VA
switching capacity active power / at DC	6 ... 30 W
product function / galvanic isolation of the outputs	Yes
Communication	
protocol / to the substation as client / is supported / IEC 60870-5-104	Yes
protocol / to the higher-level station as server / is supported / IEC 60870-5-104	Yes

protocol / to the substation as master / is supported / IEC 60870-5-103	Yes
protocol / is supported / IEC 60870-5-103 as device	Yes
protocol / to the substation as master / is supported / IEC 60870-5-101	Yes
protocol / is supported / IEC 60870-5-101 as device	Yes
protocol / to the substation as client / is supported / IEC 61850	Yes
protocol / to the higher-level station as server / is supported / IEC 61850	Yes
protocol / at the point-to-point connection / is supported / Modbus RTU as master	Yes
protocol / is supported / Modbus RTU device	Yes
protocol / is supported / Modbus TCP as client	Yes
protocol / is supported / Modbus TCP as server	Yes
protocol / is supported / DNP 3.0 serial as master	Yes
protocol / is supported / DNP 3.0 serial as device	Yes
protocol / is supported / DNP 3.0 TCP as client	Yes
protocol / is supported / DNP 3.0 TCP as server	Yes
protocol / is supported / PROFIBUS DP as master	Yes
protocol / is supported / PROFINET as master	Yes
type of mobile wireless service / is supported / GPRS	No
number of protocols / for standard application / maximum	8
number of protocols / through firmware expansion	4
number of ports / of the Ethernet interface	2
number of interfaces / serial	2
Cybersecurity	
type of communication security / Secure 104 according to IEC 62351-3	Yes
type of access control / role-based access control (RBAC)	Yes
type of system monitoring / according to SNMP	Yes
product function / logging via Security Eventlog	Yes
service / as web server / HTTPS	Yes
product feature / configurable firewall	Yes
product function / firmware identifier	Yes
Time synchronization	
time synchronization / via telecontrol protocol	Yes
time synchronization / via NTP/SNTP	Yes
time synchronization / via IRIG-B	Yes
product feature / time synchronization via IEEE 1588	Yes
Mechanical Design	
width	30 mm
height	132 mm
depth	124 mm
product feature / with display	No
fastening method / DIN-rail mounting	Yes
fastening method / wall mounting	No
fastening method / rack mounting	No
type of electrical connection	screw terminal
connectable conductor cross-section	0.2 ... 2.5 mm ²
material / of the enclosure	plastic
product feature / plug-in terminal blocks	Yes
product function / with function display	Yes
product function / status display	Yes
Degree of protection / protection class	
operating resource protection class	III
degree of pollution	2
protection class IP / on the front	IP20
Environmental conditions	
ambient temperature / during operation	-25 ... +70 °C
ambient temperature / during storage	-30 ... +85 °C

relative humidity	5 ... 95 %
mounting height in relation to mean sea level / maximum	3 000 m
air pressure / maximum	106 kPa
Approval certification	
certificate of suitability / CE marking	Yes
certificate of suitability / UL approval	Yes
Further information	

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=6MF2805-0AC00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6MF2805-0AC00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=6MF2805-0AC00

Tender specifications

<https://www.siemens.com/specifications>

Power Academy - Your training and consulting partner in the area of power transmission and distribution

<https://www.siemens.com/poweracademy>

