



 PRODUCT-DETAILS

ACS355-03E-05A6-4 Solar Pump Drive

LV AC machinery drive module, IEC: Pn 2.2 kW, 5.6 A (ACS355-03E-05A6-4 Solar Pump Drive)



General Information

Global Commercial Alias:	ACS355-03E-05A6-4 Solar Pump Drive
Product ID:	3AUA0000157191
ABB Type Designation:	ACS355-03E-05A6-4 Solar Pump Drive
EAN:	6438177325048
Catalog Description:	LV AC machinery drive module, IEC: Pn 2.2 kW, 5.6 A (ACS355-03E-05A6-4 Solar Pump Drive)
Long Description:	<p>The ACS355 drives are designed to meet the requirements of an extensive range of machinery applications in food and beverage, material handling, lifting, textile, printing, rubber and plastics, and woodworking applications.</p> <p>The drive is user-friendly, yet it provides a wide range of built-in technology such as the safe torque off functionality and sequence programming, reducing the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for speed and torque control of AC induction and permanent magnet motors.</p>
Display Name:	ACS355-03E-05A6-4 Solar Pump Drive

Ordering

Customs Tariff Number:	85044085
HS Code:	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES; Electrical transformers, static converters (for example, rectifiers) and inductors; Static converters
Invoice Description:	ACS355-03E-05A6-4 Pn 1,5kW, I2n 5,6A IP20 Solar Pump Drive
Made To Order:	No
Minimum Order Quantity:	1 piece
Order Multiple:	1 piece
Quote Only:	No
Selling Unit of Measure:	piece

Dimensions

Product Net Weight:	1.8 kg
Product Net Depth / Length:	161 mm
Product Net Height:	239 mm
Product Net Width:	70 mm
Package Level 1 Depth / Length:	344 mm
Package Level 1 Height:	132 mm
Package Level 1 Width:	217 mm
Package Level 1 Units:	1 carton

Technical

Number of Phases:	3-phase
Degree of Protection:	IP20
Enclosure Type NEMA:	Open Type
Multiple Battery Information:	No battery / cell included
Frequency (f):	50/60 Hz
Frame Size:	R1
Input Voltage (U_{in}):	380 ... 480 V
Mounting Type:	Module for cabinet building
Output Current, Normal Use (I_n):	5.6 A
Output Power, Normal Use (P_n):	2.2 kW

Environmental

WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
-----------------------	--

External Classifications and Standards

UNSPSC: 39122001

Kit Contents

Identifier	Qty
3AUA0000150422	1
3AUA0000058187	1

Categories

Products > Drives > Low Voltage AC Drives > Machinery Drives > ACS355 - Machinery Drive

Parts & Services > Drives > Services > Spares and Consumables > Parts

