



**131B7564** [↗](#)

**FC-102P55KT4E21H2XGCXXXSXXXAXBXCXXXDX**

Frequency Converter  
 FC-102P55KT4E21H2XGCXXXSXXXAXBXCXXXDX  
 VLT® HVAC Drive FC-102  
 (P55K) 55 KW / 75 HP,  
 Three phase, 380 - 480 VAC, IP21 / Type 1  
 RFI Filter  
 No brake chopper  
 Graphical Loc. Cont. Panel  
 Coated PCB, No Mains Option  
 Latest release std. SW.  
 Frame: C1  
 No A Option, No B Option  
 No C1 option, No D option

Other options according to Model Code

**Model code:** FC-102P55KT4E21H2XGCXXXSXXXAXBXCXXXDX

Danfoss VLT® HVAC Drive FC-102 Drive is dedicated to ventilation, heating, and refrigeration applications. With a wide range of powerful standard and optional features, the Drive provides the lowest overall cost of ownership.

**View Efficiency Data** [↗](#)

**PRODUCT DETAILS**

<b>Gross weight</b>		41.59 Kilogram
<b>Net weight</b>		38.59 Kilogram
<b>Volume</b>		176.054 Liter
<b>EAN</b>		5702427358096
<b>Product View (Switch)</b>	GLBL	Global (Standard)
<b>Product Group</b>	FC-	VLT® HVAC Drive FC-
<b>Series</b>	102	102
<b>Power Rating</b>	P55K	(P55K) 55 KW / 75 HP
<b>Phase</b>	T	Three phase
<b>Mains Voltage</b>	4	380 - 480 VAC
<b>Enclosure</b>	E21	IP21 / Type 1
<b>RFI Filter</b>	H2	RFI Filter
<b>Brake - Safe Stop</b>	X	No brake chopper
<b>LCP</b>	G	Graphical Loc. Cont. Panel
<b>Coating PCB</b>	C	Coated PCB
<b>Mains Option</b>	X	No Mains Option
<b>Adaptation A</b>	X	Standard Cable Entries
<b>Adaptation B</b>	X	No adaptation
<b>Software Release</b>	SXXX	Latest release std. SW.
<b>Software Language Pack</b>	X	Standard Language Pack
<b>A Option</b>	AX	No A Option
<b>B Option</b>	BX	No B Option
<b>C0 Option MCO</b>	CX	No C0 option
<b>C1 Option</b>	X	No C1 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**PRODUCT DETAILS**

<b>C Option Software</b>	XX	No software option
<b>D Option</b>	DX	No D option
<b>Frame Size</b>	C1	C1
<b>Product Catalog</b>	NO_VIEW	NO VIEW
<b>Typecode Part 1</b>		FC-102P55KT4E21H2XGC
<b>Typecode Part 2</b>		XXXSXXXXAXBXCXXXXDX
<b>Power 110% (NO) [KW]</b>	55	55
<b>Height [mm]</b>	685,0	685,0
<b>Width w/ no C options [mm]</b>	308,0	308,0
<b>Depth [mm]</b>	311,0	311,0
<b>Depth with Option A/B [mm]</b>	311,0	311,0
<b>kVA</b>	73.4	73.4
<b>Power Loss NO [W]</b>	1083	1083
<b>Power Loss NO [W]</b>	1083	1083
<b>Continuous Current (NO) [A]</b>	106	106
<b>Intermittent Current (NO) [A]</b>	117	117
<b>Continuous Current (NO) [A]</b>	105	105
<b>Intermittent Current (NO) [A]</b>	116	116
<b>Calculated Gross Weight [kg]</b>		41.59
<b>Calculated Net Weight [kg]</b>		38.59
<b>ECCN EU</b>	Y901	Y901
<b>ECCN US</b>	3A999.a	3A999.a
<b>Vendor</b>	ERR01	Cannot Determine Vendor
<b>Recommended Factory</b>	ERR01	Cannot Determine Vendor
<b>Modelcode01</b>		FC-102P55KT4E21H2XGC
<b>Modelcode02</b>		XXXSXXXXAXBXCXXXXDX
<b>Recommended Plant</b>	ERR01	ERR01

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

**Accessories**


**130B0294** [🔗](#)  
**sparepart/multi accessory bag - clips**



**130B0295** [🔗](#)  
**sparepart/terminals accessory bag**



**130B1048** [🔗](#)  
**Panel Through Mounting Kit, C1**  
 Push-through frame kit for FC size C1 Contains mounting frame, seal, Fastening material and assembly instructions.

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Accessories**

**130B1070**
**RS485 plug, FC series, 10 pcs**

10 pcs RS485 connectors for FC-series.  
Product group: R


**130B1071**
**6 Pole Connector, FC series, 10 pcs**

6-pole spring cage connectors 10 pcs


**130B1083**
**Mounting Brackets, C1**

Mounting brackets for enclosure size C1


**130B1088**
**LCP Blindcover, w/ Danfoss logo, IP20/21**

**130B1110**
**VLT® Relay Option MCB 105, uncoated**

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A


**130B1117**
**LCP Mounting Kit, w/ no LCP**

The kit includes fasteners, 3m cable and gasket - There is no LCP included.


**130B1124**
**VLT® Control Panel LCP 101, numeric**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters. Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.


**130B1125**
**VLT® General Purpose I/O MCB 101, unctd**

MCB 101 - Advanced I / O option

Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.

- 2 analog inputs 0 - 10 V.

- 2 digital outputs NPN / PNP switchable 24 V

- 1 analog output 0/4 - 20 mA

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

**130B1135** [🔗](#)**VLT® PROFINET MCA 120, uncoated**

MCA 120 PROFINET interface

- Supports operation on PROFINET network with extensive properties
- DCP support for easy setting u. Communication parameters via the PLC
- On Board web-Page with Drive Status
- Parameterization with the MCT10 software
- 2 port version, reduced external hardware

**130B1137** [🔗](#)**VLT® PTC Thermistor Card MCB 112, ctd**

MCB 112 PTC - thermistor relay MS220DA In connection with ATEX certified explosion-proof motors for full motor protection. Certified PTC sensors are the sole protection required. Integrable module with ATEX-compliant full thermal motor protection 1 PTB-certified PTC thermistor input 1 switch-off signal for using the Safe Stop function 1 logic output for error identification

**130B1143** [🔗](#)**VLT® Analog I/O Option MCB 109, unctd**

I / O expansion for FC 100, through modular technology easy to retrofit. Analog inputs/outputs galvanically isolated. Expands the analog inputs / outputs by:

3 analog inputs: 0 ... 10V / Pt1000 / Ni1000

3 analog outputs: 0 ... 10V

Time switch (RTC backup): lithium cell for 10 years

**130B1144** [🔗](#)**VLT® BACnet MCA 109, uncoated**

Open communication protocol dedicated to building automation

- Efficient integration of all parts of building automation equipment
- BACnet: standard for building automation worldwide
- International standard ISO 16484-5
- can be used in all sizes of building automation systems
- the Drive communicates easily with construction management systems running the BACnet protocol
- can be easily integrated into the network of existing control equipment

Product group: R1

**130B1156** [🔗](#)**USB extension Cable, 650mm**

USB extension kit for FC 300 cable length: 650mm for the housing size: B2, C1 and C2 screw connection M 25

**130B1170** [🔗](#)**LCP Panel Mounting Kit**

The kit includes fasteners and gasket. No LCP and no cable included.

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B1202** [🔗](#)

**VLT® DeviceNet MCA 104, coated**

MCA 104 - DeviceNet interface Option for FC300 and FC100 for mounting on the control card. Painted version



**130B1206** [🔗](#)

**VLT® LonWorks MCA 108, coated**

Lonworks interface for FC 100. With modular technology Fieldbus option that can be easily retrofitted for the decentralized integration of the Frequency converter. The fieldbus option is based on the LonWorks Technology and corresponds to the LonMark Interoperability Guide. Painted version for harsh environments

Hardware: Module technology for option slot A

Transceiver: Free topology FTT 10

Transfer rate: 78kbit / s

Protocol: Echelon LonTalk



**130B1208** [🔗](#)

**1xMCB 107 24V DC coat w. mount. brackets**

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.



**130B1210** [🔗](#)

**VLT® Relay Option MCB 105, coated**

Relay extension for FC 100 and FC 300.

Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Painted version for harsh environments,

easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A



**130B1212** [🔗](#)

**VLT® General Purpose I/O MCB 101, ctd**

MCB 101 - Advanced I / O option Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.

- 2 analog inputs 0 - 10 V.

- 2 digital outputs NPN / PNP switchable 24 V

- 1 analog output 0/4 - 20 mA with reinforced coating

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Accessories**

**130B1243**
**VLT® Analog I/O Option MCB 109, coated**

I / O extension for FC 100, easy to retrofit thanks to modular technology. Analog inputs / outputs galvanically isolated. Expands the analog inputs / outputs by: 3 analog inputs: 0 ... 10V / Pt1000 / Ni1000 3 analog outputs: 0 ... 10V Time switch (RTC backup): lithium cell for 10 years


**130B1244**
**VLT® BACnet MCA 109, coated**

A. Device profile: Application-Specific-Controller (B-ASC)

Supported objects: Analog Input, Analog Output, Analog Value, Binary Input, binary output, Binary Value, Device, Multi-State Output, Notification Class

Protocol: Building automation world standard ISO 16484-5

Data Link Layer: MS / TP 9600, 19200, 38400, 76800

Data sharing: ReadProperty-B, DS-RP-B ReadPropertyMultiple-B, DS-RPM-B WriteProperty-B, DS-WP-B

WritePropertyMultiple-B, DS-WPM-B Alarm and Notification Internal-B, AE-N-I-B

Event Notification: ACK-B, AE-ACK-B Information-B, AE-INFO-B Device and Network Dynamic Device Binding-A, DM-DDB-A

Management: Dynamic Device Binding-B, DM-DDB-B


**130B1385**
**VLT® Profibus DP V1 MCA101, unctd 5pcs**

**130B1386**
**VLT® Profibus DP V1 MCA 101, ctd, 5pcs**

**130B3910**
**Back plate IP21/Type 1, IP55/Type 12, C1**

FC 300 back cover for the devices in IP21 / 55 Case size C1


**130B4597**
**Weather shield f. outdoor instl. C1, C2**

Weather shield for enclosure sizes C1, C2

Image coming soon

**130B4847**
**extension cable for lcp+communication**

**130B5435**
**DIN Rail Mounting Kit**

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B5436** [🔗](#)  
**Side Fixture Mounting Kit**

Side Fixture Mounting Kit for enclosure size A5 / B1 / B2 / C1 / C2  
 To be used when retrofitting the following MCA options:  
 MCA 120 Profinet  
 MCA 121 EtherNet  
 MCA 122 Modbus TCP  
 MCA 123 POWERLINK  
 MCA 124 EtherCAT  
 Product group: R1



**130B7533** [🔗](#)  
**Mounting Kit C Option, B/C/D/E/F(not B3)**  
 MCF105 C Option, Mounting Kit A2 and A3



**134B0460** [🔗](#)  
**LCP 103 Wireless Communication Panel**

With VLT® Wireless Communication Panel LCP 103 you can communicate with MyDrive® Connect - an app that can be downloaded for iOS and Android based smartphones. MyDrive® Connect makes commissioning easy, monitor and maintain tasks on your frequency converter. VLT® Wireless Communication Panel LCP 103 shows the current status of the drive (On, Warning, Alarm, Wifi connection) via built-in LED. Detailed information is also available using MyDrive® Connect. Here do you have access to i.a. status, menu and alerts. You can also see graphs over the latest available data.

The new VLT® Wireless Communication Panel LCP 103 allows you to wireless communication to the following drives:

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302

[!] Note!

LCP 103 only works on frequency converters produced in 2018 (White USB stik).

Product group: R1



**134B1586** [🔗](#)  
**VLT® BACNET/IP MCA125**

The VLT® BACnet/IP MCA 125 option is a plug-and-play solution that optimizes the use of VLT® HVAC Drive together with building management systems using the BACnet/IP protocol or running BACnet on Ethernet.

The embedded three-port managed switch of the VLT® BACnet/IP MCA 125 option comprises two external and one internal Ethernet port. This switch allows the use of line structure for the Ethernet cabling. In modern installation this is becoming increasingly attractive

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Accessories**

Image coming soon

**134B1968**
**Accessory bag for frame size C1**

Accessory bag for frame size C1

Image coming soon

**134B1992**
**Control Terminals w/ screw connections**

**134B5223**
**Remote LCP unit, 3m**

Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10 ft) cable

Image coming soon

**134B5224**
**Remote LCP unit, 5m**

Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16 ft) cable

Image coming soon

**134B5225**
**Remote LCP unit, 10m**

Remote mounting kit for LCP with cover for outdoor mounting with 10 m (33 ft) cable


**134B5925**
**Pressure Transmitter**

VLT PTU 025 pressure transmitter unit for external attachment to frequency converters VLT HVAC Drive FC-102 IP55 / IP66 on one the cable entries suitable for M25 - with four pressure sensors 2x 0-500 Pa; 1x 0-1000 Pa; 1x 0-2500 Pa

- eight hose connections D 5mm

- Can be positioned 360 ° around the longitudinal axis

Software version of the frequency converter FC-102 at least 5.20 am required

Mounting thread: M25

Dimensions LxW: 155mm x 38mm (Length with hose support rail 260.5mm)

Degree of protection: IP66

Image coming soon

**134B6880**
**VLT Progr. Contr. MCA 301, coated**

Image coming soon

**134B6883**
**VLT Progr. Contr. MCB 301, coated**

Image coming soon

**134B7207**
**cable clamp/d=44-48 k48b**

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image coming soon

**134B7209** [🔗](#)  
**cable clamp/d=36-40 k40b**



**134B7466** [🔗](#)  
**Option A Ethernet Package**



**134B8492** [🔗](#)  
**Transducer 0-10g, 4-20mA; HS-22B50**



**134B8493** [🔗](#)  
**Transducer 0-25mm/s RMS 4-20mA**  
 CBM Transducer 0-25mm/s RMS 4-20mA



**134B8494** [🔗](#)  
**Transducer w, temp 0-25mm/s RMS 4-20mA**



**134B8496** [🔗](#)  
**CABLE ASSY 10M, STRAIGHT SOCKET CONNETC.**

Image coming soon

**134B8497** [🔗](#)  
**Cable assy, M12 female connec.10m screen**



**134B8814** [🔗](#)  
**VLT® PROFINET MCA120 coated 5pcs**



**134B9400** [🔗](#)  
**Pressure Sensor 7245T 2x500Pa & PT1000**  
 DUAL AIR PRESSURE SENSOR ±500PA Temperature drift: ± 0.1% per °C/°F  
 Zero point offset: ± 10 % of measuring range  
 Above-/below-pressure: max. ± 50 kPa / ± 200 inWC  
 Power: 24VAC (± 20%) & (>>>)>0,2W / 15...36VDC  
 Operation temperature: -30...+70 °C / -22...+158 °F  
 Media temperature -20...+50 °C / -4...+122 °F  
 T2-IP65 plastic housing with two M16 cable glands one M12 for temperature  
 Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**134B9401** [🔗](#)

**Pressure Sensor 7249T 500/7000Pa & PT1000**

DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$  Temperature drift:  $\pm 0.1\%$  per  $^{\circ}\text{C}$  #  
 $^{\circ}\text{F}$

Zero point offset:  $\pm 10\%$  of measuring range

Above- # below-pressure: max.  $\pm 50\text{ kPa}$  /  $\pm 200\text{ inWC}$

Power:  $24\text{VAC}$  ( $\pm 20\%$ ) &lt;0,2W /  $15\text{...}36\text{VDC}$

Operation temperature:  $-30\text{...}+70\text{ }^{\circ}\text{C}$  /  $-22\text{...}+158\text{ }^{\circ}\text{F}$

Media temperature  $-20\text{...}+50\text{ }^{\circ}\text{C}$  /  $-4\text{...}+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with two M16 cable glands one M12 for  
 temperature

Housing dimensions:  $126 \times 90 \times 50\text{ mm}$  /  $4.96 \times 3.54 \times 1.97\text{ in}$



**134B9402** [🔗](#)

**Pressure Sensor 7247T 2x7000Pa & PT1000**

DUAL AIR PRESSURE SENSOR  $\pm 7000\text{Pa}$  Temperature drift:  $\pm 0.1\%$  per  $^{\circ}\text{C}$  #  
 $^{\circ}\text{F}$

Zero point offset:  $\pm 10\%$  of measuring range

Above- # below-pressure: max.  $\pm 50\text{ kPa}$  /  $\pm 200\text{ inWC}$

Power:  $24\text{VAC}$  ( $\pm 20\%$ ) &lt;0,2W /  $15\text{...}36\text{VDC}$

Operation temperature:  $-30\text{...}+70\text{ }^{\circ}\text{C}$  /  $-22\text{...}+158\text{ }^{\circ}\text{F}$

Media temperature  $-20\text{...}+50\text{ }^{\circ}\text{C}$  /  $-4\text{...}+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with two M16 cable glands one M12 for  
 temperature

Housing dimensions:  $126 \times 90 \times 50\text{ mm}$  /  $4.96 \times 3.54 \times 1.97\text{ in}$



**134B9404** [🔗](#)

**Pressure Sensor 7225 2x500Pa, Analog**

DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$   $\pm 500\text{Pa}$ , ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2  
 automated analogue output signals in a resistant IP65 plastic housing  
 with quick-locking screws, connection nozzles for pressure hose ( $\varnothing 6\text{ mm}$ )  
 and a M16 cable gland for cable connection. The pressure measuring  
 transducer automatically detects the required output type and converts  
 the measurands into the required standard signal of  $0\text{--}10\text{ V}$  or  $4\text{...}20\text{ mA}$ .

Pressure range selection:  $\pm 500\text{ Pa}$  –  $0\text{...}100\text{Pa}$  /  $200\text{Pa}$  /  $300\text{Pa}$  /  $500\text{Pa}$

Accuracy:  $500\text{ Pa}$  typical  $\pm 13\text{ Pa}$

Zero point offset:  $\pm 10\%$  of measuring range

Above- # below-pressure: max.  $\pm 50\text{ kPa}$

Power:  $24\text{VAC/DC}$  ( $\pm 10\%$ ) &lt;1,3W,

Output: automatically switching  $0\text{--}10\text{ V}$  #  $4\text{...}20\text{ mA}$

Working resistance:  $R_a$  (ohms) =  $25\text{...}450\text{ Ohm}$  (at I output)

Load resistance:  $R_L$  &gt;  $15\text{ kOhm}$  (at U output)

Operation / Media temperature:  $-20\text{...}+50\text{ }^{\circ}\text{C}$  /  $-4\text{...}+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions:  $126 \times 90 \times 50\text{ mm}$  /  $4.96 \times 3.54 \times 1.97\text{ in}$

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**134B9405**

**Pressure Sensor 7229 500/7000Pa, Analog**

DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$   $\pm 7000\text{Pa}$ , ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing$  6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection:  $\pm 500\text{ Pa} - 0 \dots 100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$  Pressure range selection:  $\pm 7000\text{ Pa} - 0 \dots 1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$

Accuracy: 500 Pa typical  $\pm 13\text{ Pa}$

Accuracy: 7000 Pa typical  $\pm 105\text{ Pa}$

Zero point offset:  $\pm 10\%$  of measuring range

Above- # below-pressure: max.  $\pm 50\text{ kPa}$

Power: 24VAC/DC ( $\pm 10\%$ ) &lt;1,3W,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance:  $R_a$  (ohms) = 25...450 Ohm (at I output)

Load resistance:  $R_L$  &gt; 15 kOhm (at U output)

Operation / Media temperature:  $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in



**134B9406**

**Pressure Sensor 7227 2x7000Pa, Analog**

DUAL AIR PRESSURE SENSOR  $\pm 7000\text{Pa}$   $\pm 7000\text{Pa}$ , ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing$  6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA.

Pressure range selection:  $\pm 7000\text{ Pa} - 0 \dots 1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$

Accuracy: 7000 Pa typical  $\pm 105\text{ Pa}$

Zero point offset:  $\pm 10\%$  of measuring range

Above- # below-pressure: max.  $\pm 50\text{ kPa}$

Power: 24VAC/DC ( $\pm 10\%$ ) &lt;1,3W,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance:  $R_a$  (ohms) = 25...450 Ohm (at I output)

Load resistance:  $R_L$  &gt; 15 kOhm (at U output)

Operation / Media temperature:  $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**134B9407**

**Airflow Sensor KFTF Temp & Humidity**

DUCT HUMIDITY- AND TEMPERATURE SENSORS KFTF-MB

Calibratable duct humidity and temperature sensor KFTF-T3 ( $\pm 2.0\%$ ) with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection and a plastic sinter filter (exchangeable). Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ( $-35...+80\text{ }^\circ\text{C}$ ) inside a tube, including various parameters in the humidity measurement. The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices.

International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) /  $-35...+80\text{ }^\circ\text{C}$  (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical  $\pm 2.0\%$  (20...80 % RH) at  $+25\text{ }^\circ\text{C}$ , otherwise  $\pm 3.0\%$

Deviation, temperature: typical  $\pm 0.2\text{ K}$  at  $+25\text{ }^\circ\text{C}$

Zero point offset:  $\pm 10\%$  RH (humidity) /  $\pm 5\text{ }^\circ\text{C}$  (temperature)

Power: 24VAC ( $\pm 20\%$ ) / 15...36VDC - 24DC &lt;1,2W

Operation temperature:  $-30...+70\text{ }^\circ\text{C}$  /  $-22...+158\text{ }^\circ\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

Image coming soon

**134B9408**

**Airflow Sensor 8148 Temp&Humidity&500Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS  $\pm 500\text{Pa}$ -MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ( $-35...+80\text{ }^\circ\text{C}$ ) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max.  $\pm 500\text{ Pa}$ ) with connection nozzles for pressure hose ( $\varnothing 6\text{ mm}$ ). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) /  $-35...+80\text{ }^\circ\text{C}$  /  $-31... +176\text{ }^\circ\text{F}$  (temperature)

Medium: clean air and non-aggressive, non-combustible gases Deviation, humidity: typical  $\pm 2.0\%$  (20...80 % RH) at  $+25\text{ }^\circ\text{C}$  /  $+77\text{ }^\circ\text{F}$ , otherwise  $\pm 3.0\%$  Deviation, temperature: typical  $\pm 0.2\text{ K}$  at  $+25\text{ }^\circ\text{C}$  /  $\pm 0.4\text{ }^\circ\text{F}$  at  $+77\text{ }^\circ\text{F}$

Pressure range:  $\pm 500\text{ Pa}$

Accuracy: 500 Pa/2.0 inWC: typical  $\pm 13\text{ Pa}$  at  $+25\text{ }^\circ\text{C}$  /  $\pm 0.05\text{ inWC}$  at  $+77\text{ }^\circ\text{F}$  Above- #

below-pressure: max.  $\pm 50\text{ kPa}$  Power: 24VAC ( $\pm 20\%$ ) / 15...36VDC - 24DC &lt;0,2W

Operation temperature:  $-30...+70\text{ }^\circ\text{C}$  /  $-22...+158\text{ }^\circ\text{F}$

Media temperature  $-20...+50\text{ }^\circ\text{C}$  /  $-4...+122\text{ }^\circ\text{F}$  IP65 plastic housing two M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image coming soon

**134B9409**

**Airflow Sensor 8147 Temp&Humidity&7000Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±7000PA-MB  
 Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 7000 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).  
 Measuring range: 0...100 % RH (humidity) / - 35...+80°C /-31... +176°F (temperature)  
 Medium: clean air and non-aggressive, non-combustible gases  
 Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F , otherwise ± 3.0 %  
 Deviation, temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F  
 Pressure range: ± 7000 Pa  
 Accuracy: 7000 Pa/28 inWC: typical ± 105 Pa at +25 °C / ± 0.12 inWC at +77 °F  
 Above- # below-pressure: max. ± 50 kPa  
 Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;0,2W  
 Operation temperature: -30...+70 °C / -22...+158 °F  
 Media temperature -20...+50 °C / -4...+122 °F IP65 plastic housing two M16 cable glands  
 Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in



**134B9410**

**Wall Sensor ATM2 Temperature**

OUTSIDE / WET ROOM TEMPERATURE SENSOR ATM2-MB  
 Calibratable outside temperature sensor ATM2, PT1000 measure temperature (-50...+150 °C), with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M20 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).  
 Sensor type: PT1000 class B (DIN EN 60751)  
 Measuring range: - 50...+150°C /-31... +176°F  
 Deviation: typical ± 0.2 K at +25 °C / ± 77 °F  
 Zero point offset: ± 10 °C / ± 50 °F  
 Ambient temperature: Measuring transducer -30...+70 °C /-22... +158°F  
 Medium: clean air and non-aggressive, non-combustible gases  
 Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;1,2W  
 Operation temperature: -30...+70 °C / -22...+158 °F  
 T3-IP65 plastic housing with two M20 cable glands  
 Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**134B9411** [🔗](#)

**Wall Sensor AFTF Temp & Humidity**

ON-WALL- HUMIDITY- AND TEMPERATURE SENSORS AFTF-MB

Calibratable outside humidity and temperature sensor AFTF, detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C), including various parameters in the humidity measurement. Applied in clean air and non-aggressive, dust-free environment. With a Modbus connection in a resistant IP65 plastic housing and M20 cable gland for cable connection, with quick-locking screws and an exchangeable plastic sinter filter. International SI units (default) can be changed to imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80 °C (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25 °C, otherwise ± 3.0 %

Deviation, temperature: typical ± 0.4 K at +25 °C / ± 77 °F

Zero point offset: ± 10 % RH (humidity) / ± 5 °C (temperature)

Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;1,2W

Operation temperature: -30...+70 °C / -22...+158 °F

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in



**134B9412** [🔗](#)

**Airflow Sensor TF65 PT1000 Temperature**

DUCT TEMPERATURE SENSOR TF 65

The TF 65 temperature measuring transducer is a PT1000 class B resistance sensor with passive output. Measuring range from -30...+150 °C. In a resistant IP67 plastic housing and M16 cable gland for cable connection and a straight protective measuring tube and a mounting flange.

Sensor type: PT1000 class B (DIN EN 60751) 1000ohm at 0°C ± 0,3 K

Measuring range: -30...+150 °C/ -22...+302 °F

Ambient temperature: -20...+100 °C / -4...+212 °F

Testing current: &lt; 0.6 mA

Insulating resistance: 100 M#, at +20 °C (500V DC)

Connection type: 2-wire connection

Measuring tube: stainless steel, V4A (1.4571), Ø 6 mm, inserted length = 300 mm / 11.8 in

T1-IP67 plastic housing with a M16 cable glands and a mounting flange.

Housing dimensions: 72 x 64 x 37.8 mm / 2.83 x 2.52 x 1.49 in

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

**134B9413** **Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas

temperature dependence:  $\pm 5$  ppm pro  $^{\circ}\text{C}$  or  $\pm 0,5$  % of measured value pro  $^{\circ}\text{C}$  (whichever is higher) pressure dependence:  $\pm 0.13$  % per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ( $\pm 10\%$ ) 24DC &lt;1,6W

Operation temperature:  $-10...+60$   $^{\circ}\text{C}$  /  $14...+140$   $^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**134B9414**

**Antifreeze Thermostat FS20, 0/+15C**

TWO-PHASE FROST PROTECTION THERMOSTATS FS-20-UW

Electronic frost protection thermostat or frost monitor with switching relay output, continuous temperature and valve output (summation output 0–10 V) and control and cascading output (0–10 V), optionally with connection for a heating element. A IP65 resistant plastic housing with display with the actual temperature, measuring range, overrange/underrange of the set switch point (frost protection temperature) and alarm indicator for "frost" or "error" (capillary breakage, overvoltage/undervoltage), quick-locking screws and a fully active sensor rod made of copper. The delivery scope includes a set of MK-05-K mounting clamps for expert attachment of the sensor rod.

Measuring range: 0...+15 °C / 32...+59 °F

Accuracy: typical ± 1 K (at +10 °C)

Sensor type: 3m Copper rod active along the entire sensor length, min. response length of 25 cm

Input: 1 x 0 -10 V control input DDC

1 x 0 -10 V output valve (frost signal with control voltage and cascading)

1 x potential-free changeover contact (24 V), range of adjustment 0...+15 °C

Current consumption: max. 100 mA at 24 V DC

Load resistance: RL > 50 kOhm

Ambient temperature: -15...+50 °C / 5...+122 °F (Housing) -20...+60 °C / -4...+140 °F Sensor and capillary tube > 20 cm from the housing.

Power: 24VAC/DC (± 10%) 24DC < 2,4W

T2-IP65 plastic housing with three-line display 70x40 mm (WxH), a M16 cable glands and MK-05-K mounting clamps.

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in



**175N2584**

**VLT® EtherNet/IP Modbus TCP gateway**

Image coming soon

**175U0009**

**Mounting bracket Kit, 216 x 30 x 18mm**

Mounting angle for flatpack resistor 200W



**175Z0929**

**LCP Cable, 3m**

Cable for control panel (LCP), 3 meters Works with the following LCP:

Alphanumeric control panel LCP3 - 175N0131

VLT® LCP 102 Graphic Display - 130B1107

VLT® LCP 101 Numeric Display - 130B1124

VLT® LCP 102 Graphic display IP66 - 130B1078

Product group: F1

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

---



**176F4106** [🔗](#)

**Fieldbus plate, highpower, IP20, 10 pcs**

---



**185B0009** [🔗](#)

**FC-102 Demo Case - 120 Vac Supply**

Elevate your sales presentations and on-site training with this high-impact, portable VFD demo kit. Showcasing the Danfoss VLT® FC 102 drive, this suitcase provides a dynamic, hands-on experience for demonstrating the benefits of variable frequency drives in motor control. The integrated flywheel and controls simulate a mechanical load, offering a realistic, visual representation of VFD capabilities 120VAC Supply (Standard outlet in North America) Dimensions: 24.75 in. x 19.50 in. x 12 in. (63 cm x 50 cm x 30 cm)

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---