



**080G0073** 

**Programming key, MMIMYK**

Function: Programmable controller, Supply voltage [V] AC: 24, Communication type: TTL; CANBUS; RS485; MODBUS, Packing format: Single pack, Quantity per packing format: 1

**PRODUCT DETAILS**

<b>Gross weight</b>	0.246 Kilogram
<b>Net weight</b>	0.181 Kilogram
<b>Volume</b>	1.109 Liter
<b>EAN</b>	5702428170680
<b>Type</b>	MMIMYK
<b>Product group</b>	Programmable controllers
<b>Product Name Description</b>	Programming key
<b>1 Primary battery SUM weight Kg</b>	0.001
<b>1 Primary battery weight Kg</b>	0.001
<b>Approval</b>	CE GOST R
<b>Battery qty</b>	1
<b>Battery type or Name</b>	Lithium coin cell (CR1620)
<b>Buzzer</b>	Yes
<b>CE mark</b>	Yes
<b>China RoHS compliance</b>	Out of scope
<b>Communication type</b>	CANBUS MODBUS RS485 TTL
<b>Connector kit Code No.</b>	080G0176
<b>Connector kit included</b>	Yes
<b>Contains batteries</b>	Yes
<b>Display type</b>	OLED
<b>Division</b>	25
<b>EEE category</b>	5 small equipment (any external dimension &lt; 50 cm)
<b>Enclosure rating IP</b>	IP20
<b>EU RoHS compliance</b>	Yes
<b>EU RoHS exemption clause</b>	No
<b>Frequency [Hz]</b>	50/60 Hz
<b>Function</b>	Programmable controller
<b>Further information</b>	Memory card, data logger
<b>Identical product</b>	080G0154
<b>In scope of WEEE</b>	Yes
<b>Mounting method</b>	DIN rail Portable
<b>Packing format</b>	Single pack
<b>PFAS content [Yes/No]</b>	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**PRODUCT DETAILS**

<b>Power consumption [W]</b>	2.5 W
<b>Product accessories</b>	Electron. control accessories
<b>Quantity per packing format</b>	1 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1) Lead titanium zirconium oxide (CAS no. 12626-81-2) 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol (CAS no. 119-47-1) 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol (CAS no. 79-94-7) 1, 2-dimethoxyethane, ethylene glycol dimethyl ether (EGDME) (CAS no. 110-71-4) Potassium nonafluoro-1-butanesulfonate (CAS no. 29420-49-3) Cadmium oxide (CAS no.1306-19-0)
<b>Real time clock</b>	Yes
<b>SCIP dossier no.</b>	8ffe0b17-a5c2-4a33-b1d7-026f8a42926d
<b>SCIP dossier product name</b>	MCX-MMILDS,CSTFR1 & MMIMYK
<b>Serviceable</b>	No
<b>Supply voltage [V] AC</b>	24 V
<b>Supply voltage [V] DC</b>	12 V
<b>Type designation</b>	MMIMYK4501260

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

**Accessories**

**We're sorry, but the requested information is currently unavailable.**

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit [store.danfoss.com](https://store.danfoss.com).

Thank you for your understanding.

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.