

**060G2421****Pressure transmitter, MBS 4010, 0 bar - 1 bar, 0 psi - 14.5 psi**

Pressure reference: Gauge (relative), Output signal: Current, Electrical connection: Angular connector, Pressure connection type: G, Pressure connection size: 1, Specification key: MBS 4010-1011-A1CB11-2

**PRODUCT DETAILS**

<b>Gross weight</b>	0.368 Kilogram
<b>Net weight</b>	0.344 Kilogram
<b>Volume</b>	0.477 Liter
<b>EAN</b>	5702423085705
<b>+ supply</b>	Pin 1
<b>- common</b>	Pin 2
<b>Accuracy, max. [±FS%]</b>	1 %
<b>Accuracy, typical [±FS%]</b>	0.2 %
<b>Adj. zero point and span</b>	No
<b>Ambient temperature range [°C]</b> [max]	85 °C
<b>Ambient temperature range [°C]</b> [min]	-10 °C
<b>Ambient temperature range [°F]</b> [max]	185 °F
<b>Ambient temperature range [°F]</b> [min]	14 °F
<b>Approval</b>	ATEX CE
<b>Approval comments</b>	ATEX Ex ec IIA T4 Gc
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Yes
<b>Compensated temp. range [°C]</b> [max]	80 °C
<b>Compensated temp. range [°C]</b> [min]	0 °C
<b>Compensated temp. range [°F]</b> [max]	176 °F
<b>Compensated temp. range [°F]</b> [min]	32 °F
<b>Contain batteries</b>	No
<b>EEE category</b>	5 small equipment (any external dimension &lt; 50 cm)
<b>Electrical conn. Male/Female</b>	Male and Female
<b>Electrical connection</b>	Angular connector
<b>Electrical connection size</b>	Pg 9
<b>Electrical connection standard</b>	EN 175301-803-A
<b>Enclosure rating IP</b>	IP65
<b>EU RoHS compliance</b>	Yes with exemptions

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Pressure transmitter, MBS 4010, 0 bar - 1 bar, 0 psi - 14.5 psi**
**PRODUCT DETAILS**

<b>EU RoHS exemption clause</b>	6(c)
<b>Flush diaphragm</b>	Yes
<b>High Clipping Level</b>	22.4
<b>In scope of WEEE</b>	Yes
<b>International Article Number</b>	5702423085705
<b>Intrinsically safe</b>	No
<b>Low Clipping level</b>	3.6
<b>Medium temperature range [°C] [max]</b>	85 °C
<b>Medium temperature range [°C] [min]</b>	-40 °C
<b>Medium temperature range [°F] [max]</b>	185 °F
<b>Medium temperature range [°F] [min]</b>	-40 °F
<b>Non-linearity BFSL [±FS%]</b>	0.2 %
<b>Output signal</b>	Current
<b>Output signal [mA] [max]</b>	20 mA
<b>Output signal [mA] [min]</b>	4 mA
<b>Overload pressure max. [bar]</b>	2 bar
<b>Packing format</b>	Multi pack
<b>Pressure connection HEX [mm]</b>	41 mm
<b>Pressure connection size</b>	1
<b>Pressure connection standard</b>	ISO 228-1
<b>Pressure connection type</b>	G
<b>Pressure Male/Female</b>	Male
<b>Pressure range [bar] [max]</b>	1 bar
<b>Pressure range [bar] [min]</b>	0 bar
<b>Pressure range [psi] [max]</b>	14.5 psi
<b>Pressure range [psi] [min]</b>	0 psi
<b>Pressure reference</b>	Gauge (relative)
<b>Product group</b>	Sensors
<b>Product Name Description</b>	Pressure transmitter
<b>Pulse-snobber</b>	No
<b>Quantity per packing format</b>	12 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>Response time max. [ms]</b>	4 ms
<b>SCIP dossier no.</b>	16d2efc6-64f3-4a4e-ae98- a3fd7ce0218d
<b>SCIP dossier product name</b>	AKS/MBS
<b>Specification key</b>	MBS 4010-1011-A1CB11-2
<b>Supply voltage [V] DC [max]</b>	32 V
<b>Supply voltage [V] DC [min]</b>	9 V
<b>Type</b>	MBS 4010

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

**For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**060G2501** [🔗](#)

**Accessories, sensors, Welding nipple**

Used for product: MBS 4510, Packing format: Multi pack, Quantity per packing format: 60



**060G2502** [🔗](#)

**Accessories, sensors, Process con. adapter**

Process con. adapter, Parts included: Clamp 1½" G1, Used for product: MBS 4510, Packing format: Multi pack, Quantity per packing format: 45



**060G2503** [🔗](#)

**Accessories, sensors, Process con. adapter**

Process con. adapter, Parts included: Adapter 1½" SMS1145, Used for product: MBS 4510, Packing format: Multi pack, Quantity per packing format: 45



**060G2505** [🔗](#)

**Accessories, sensors, Process con. adapter**

Process con. adapter, Parts included: Adapter DN 40 Dairy con., Used for product: MBS 4510, Packing format: Multi pack, Quantity per packing format: 45



**060G2506** [🔗](#)

**Accessories, sensors, Process con. adapter**

Process con. adapter, Parts included: Adapter DN 50 Dairy con., Used for product: MBS 4510, Packing format: Multi pack, Quantity per packing format: 20



**060G2510** [🔗](#)

**Accessories, sensors, Process con. adapter**

Process con. adapter, Parts included: Clamp 2", Used for product: MBS 4510, Packing format: Multi pack, Quantity per packing format: 24



**060G2850** [🔗](#)

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.