



44506-7410 ER1032-042MEL

Safety rope pull E-stop switch, up to 200 m, 4NC + 2NO, M20 wiring entry (4x), 24 VDC indicator beacon flashing, both-sided

Specifications

Number of contacts, normally-open	2
Number of contacts, normally-closed	4
Max. length of pull cord	125 m
Number of actuation directions	2
Mounting position	Center
Material housing	Diecast aluminium
Color	Yellow
E-stop button	Included
LED indicator	✓
With tension indication	✓
Number of conduits	4
Conduit size	M20
Ambient temperature	-25-80 °C
Degree of protection (IP)	IP67
Degree of protection (NEMA)	6

Accessories



44506-2720 RK20

Safety rope pull E-stop switch accessory, rope kit 20m



44506-2750 RK50

Safety rope pull E-stop switch accessory, rope kit 50m



44506-2780 RK80

Safety rope pull E-stop switch accessory, rope Kit 80m

Downloads

CAD Library



**ER1032 Rope Pull
Emergency Stop Switch**
Datasheet

EN PDF 642 KB



Machine Safety
Catalogue

EN PDF 9.91 MB



**Safety Component
Selection Guide EU**
Brochure

EN PDF 5.26 MB



**Safety Solution
Advanced Guide**
Guide

EN PDF 2.57 MB



Safety Solution Basic
Guide

EN PDF 14.4 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 19 March, 2026. [Click here for terms of use.](#)

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU