

fixed-mounted circuit breaker 3-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=66kA at 500V frnt.conn. top/bot. dual-hole Overcurrent release ETU 25 LSI protection adjustable 0.4-1 in Motorized/manual operating mechanism with spring charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC 50/60 Hz 230 V, 220 V DC without 1st auxiliary release With 2nd auxiliary release "R", F3 Undervoltage, instant. 24 V DC 2NO+2NC K07= Tripped signaling contact, 1 CO not possible with option F02 S08= RONIS locking device in Off position (safe OFF/disconnector functionality) Disconnector condition in compliance with IEC 60947-2 Disconnector condition in compliance with IEC 60947-2

| Model | |
|---|---|
| design of the product | IEC 60947-2 |
| design of the actuating element | Pushbutton |
| type of the driving mechanism | Manual/motorized operating mechanism with mechanical and electrical closing |
| type of the driving mechanism / motor drive | Yes |
| design of the overcurrent release | ETU25B |
| General technical data | |
| number of poles | 3 |
| size of the circuit-breaker | 2 |
| utilization category | B |
| Voltage | |
| insulation voltage / rated value | 1 000 V |
| operating voltage | |
| • at AC / at 50/60 Hz / rated value | 690 V |
| Protection class | |
| protection class IP | IP20 |
| protection class IP / on the front | IP20 |
| protection function of the overcurrent release | LSI |
| Dissipation | |
| power loss [W] | |
| • for rated value of the current / at AC / in hot operating state / per pole | 90 W |
| • maximum | 270 W |
| Main circuit | |
| operating frequency | |
| • 1 / rated value | 50 Hz |
| • 2 / rated value | 60 Hz |
| Auxiliary circuit | |
| number of NC contacts / for auxiliary contacts | 2 |
| number of NO contacts / for auxiliary contacts | 2 |
| Suitability | |
| suitability for use | Plant / motor protection |
| Adjustable parameters | |
| adjustable current response value current / of the current-dependent overload release / initial value | 1 000 A |
| Product details | |
| product component | |
| • trip indicator | Yes |
| • voltage trigger | No |
| • undervoltage release | Yes |
| design of the auxiliary switch | 2 NO + 2 NC |
| product extension / optional / motor drive | No |
| Product function | |
| product function | |

| | |
|---|--|
| • grounding protection | No |
| • phase failure detection | Yes |
| Display and operation | |
| display version | without display |
| Short circuit | |
| operating short-circuit current breaking capacity (Ics) | |
| • at 415 V / rated value | 66 kA |
| • at 500 V / rated value | 66 kA |
| • at 690 V / rated value | 50 kA |
| maximum short-circuit current breaking capacity (Icu) | |
| • at 415 V / rated value | 66 kA |
| • at 500 V / rated value | 66 kA |
| • at 690 V / rated value | 50 kA |
| Connections | |
| arrangement of electrical connectors / for main current circuit | Main connection top front/bottom double hole |
| type of electrical connection / for main current circuit | busbar connection |
| Mechanical Design | |
| height | 512 mm |
| width | 460 mm |
| depth | 379 mm |
| fastening method | fixed mounting |
| Net Weight | 59 kg |
| Environmental conditions | |
| ambient temperature / during operation | |
| • minimum | -20 °C |
| • maximum | 70 °C |
| ambient temperature / during storage | |
| • minimum | -40 °C |
| • maximum | 70 °C |
| Further information | |
| Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 | |
| Information for data generation and storage https://support.industry.siemens.com/cs/ww/en/view/109995012 | |
| Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/lowvoltage/catalogs | |
| Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1225-2CB34-4AJ2-Z K07+S08 | |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3WL1225-2CB34-4AJ2-Z K07+S08 | |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1225-2CB34-4AJ2-Z K07+S08 | |
| CAX-Online-Generator https://www.siemens.com/cax | |
| Tender specifications https://www.siemens.com/specifications | |
| Characteristic curves <a haupt"><="" href="https://curves.simarisiemens.com/curves/<mmp_prod_noCOMP=" mmp_prod_no>"="">https://curves.simarisiemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no> | |



