




---

 PRODUCT-DETAILS

## S201L-C10NA

### Miniature Circuit Breaker - S200L - 1P+N - 10 A - C - (AC) 4.5 kA




---

**General Information**

<b>Extended Product Type:</b>	S201L-C10NA
<b>Product ID:</b>	2CDS241801R0104
<b>EAN:</b>	4016779598378
<b>Catalog Description:</b>	Miniature Circuit Breaker - S200L - 1P+N - 10 A - C - (AC) 4.5 kA
<b>Long Description:</b>	S201L-C 10 NA MiniCircuitBreaker C-Char.,4,5kA,10A,1P,+NA
<b>Display Name:</b>	S201L-C10NA

---

**ABB EcoSolutions**

<b>ABB EcoSolutions:</b>	Yes
<b>Recyclability Rate of the Product acc. to EN45555:</b>	Design for Closing Resource Loops - Standard EN45555 - 80.7 %
<b>ABB Site Meeting Group Waste To Landfill Target:</b>	No non-hazardous waste is sent to a landfill
<b>Extended Product Lifetime:</b>	Product Durability
<b>End Of Life Disassembling Instructions:</b>	9AKK108468A3132

Environmental Product Declaration - EPD: 9AKK108467A7832

## Technical

<b>Dielectric Test Voltage:</b>	50 / 60 Hz - 1 min 2 kV
<b>Rated Ultimate Short-Circuit Breaking Capacity (<math>I_{cu}</math>):</b>	(133 V AC) 10 kA (230 / 400 V AC) 6 kA (230 V AC) 6 kA (230 V) 6 kA (400 V) 6 kA
<b>Rated Service Short-Circuit Breaking Capacity (<math>I_{cs}</math>):</b>	(133 V AC) 7.5 kA (230 V AC) 4.5 kA
<b>Power Supply Connection:</b>	Arbitrary
<b>Contact Position Indication:</b>	ON / OFF
<b>Energy Limiting Class:</b>	3
<b>Electrical Endurance:</b>	20000 AC cycle
<b>Mechanical Endurance:</b>	20000 cycle
<b>Number of Protected Poles:</b>	1
<b>Number of Poles:</b>	1P+N
<b>Position of Neutral Terminals:</b>	Right
<b>Tightening Torque:</b>	2.8 N·m
<b>Actuator Type:</b>	Toggle
<b>Screw Terminal Type:</b>	Failsafe Bi-directional Cylinder-lift Terminal
<b>Actuator Marking:</b>	I / O
<b>Actuator Material:</b>	Insulation Group II, Black, Sealable
<b>Recommended Screw Driver:</b>	Pozidriv 2
<b>Accessories Available:</b>	Yes
<b>Connecting Capacity:</b>	Busbar 10/10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 16 mm <sup>2</sup> Flexible 0.75 ... 16 mm <sup>2</sup> Rigid 0.75 ... 25 mm <sup>2</sup> Stranded 0.75 ... 25 mm <sup>2</sup>
<b>Installation Size:</b>	acc. to DIN 43880 1
<b>Wire Stripping Length:</b>	12.5 mm
<b>Terminal Type:</b>	Screw Terminals

## Electrical

<b>Tripping Characteristic:</b>	C
<b>Rated Operational Voltage:</b>	acc. to IEC 60898-1 230 V AC acc. to IEC 60898-1 230 V acc. to IEC 60947-2 230 V AC
<b>Operational Voltage:</b>	Maximum (Incl. Tolerance) 253 V AC Minimum 12 V AC
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	acc. to IEC/EN 60664-1 440 V
<b>Rated Impulse Withstand Voltage (<math>U_{imp}</math>):</b>	4 kV at 2000 m 5 kV at Sea Level 6.2 kV

<b>Input Voltage Type:</b>	AC
<b>Rated Current (I<sub>n</sub>):</b>	10 A
<b>Rated Short-Circuit Capacity:</b>	(AC) 4.5 kA (DC) 4.5 kA (230 / 400 V AC) 4.5 kA (230 V AC) 4.5 kA (230 V) 4.5 kA (400 V) 4.5 kA
<b>Rated Conditional Short-Circuit Current (I<sub>nc</sub>):</b>	(230 V) 6 kA (400 V) 6 kA
<b>Rated Frequency (f):</b>	50 / 60 Hz
<b>Power Loss:</b>	4.2 W at Rated Operating Conditions per Pole 2.1 W
<b>Overvoltage Category:</b>	III
<b>I<sup>2</sup>t Characteristic:</b>	9AKK107992A5102

## Design

<b>Housing Material:</b>	Insulation Group I, RAL 7035
--------------------------	------------------------------

## Technical UL/CSA

<b>Connecting Capacity UL/CSA:</b>	Busbar 18-8 AWG Conductor 18-4 AWG
------------------------------------	---------------------------------------

## Material Compliance

<b>RoHS Declaration:</b>	9AKK108472A0372
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
<b>RoHS Date:</b>	20260312
<b>REACH Declaration:</b>	9AKK107492A1906
<b>REACH Information:</b>	False - does not contain substances > 0.1 mass percentage
<b>REACH Date:</b>	20260312
<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108468A3363
<b>Toxic Substances Control Act - TSCA:</b>	9AKK108468A8104
<b>SCIP:</b>	e6800e55-46b1-49a3-881b-0f66d0e903ad Germany
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)
<b>WEEE B2C / B2B:</b>	Business To Business

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Storage -40 ... +70 °C
<b>Reference Ambient Air Temperature:</b>	30 °C

<b>Degree of Protection:</b>	IP20 IP40 Enclosure with Cover IP40
<b>Pollution Degree:</b>	3
<b>Environmental Conditions:</b>	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
<b>Resistance to Vibrations:</b>	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	25g 2 shocks 13 ms
<b>Environmental Information:</b>	2CDK400030D0201

---

## Dimensions

<b>Width in Number of Modular Spacings:</b>	2
<b>Product Net Width:</b>	35 mm
<b>Product Net Height:</b>	88 mm
<b>Product Net Depth / Length:</b>	69 mm
<b>Product Net Weight:</b>	0.217 kg
<b>Pole Net Weight:</b>	0.125 kg
<b>Built-In Depth (t<sub>2</sub>):</b>	69 mm
<b>Dimension Diagram:</b>	2CDC022007F0010

---

## Ordering

<b>Package Level 1 Units:</b>	carton 5 piece
<b>Package Level 1 Gross Weight:</b>	1.125 kg

---

## Certificates and Declarations

<b>Declaration of Conformity - CE:</b>	2CDK403001D0607
--	-----------------

---

## Installation

<b>Instructions and Manuals:</b>	2CDS207104P0002
<b>Mounting Type:</b>	DIN-Rail
<b>Mounting on DIN Rail:</b>	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
<b>Mounting Position:</b>	any

---

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	9AKK107046A0423
---	-----------------

---

## External Classifications and Standards

---

**ETIM 9:** EC000042 - Miniature circuit breaker (MCB)

**ETIM 10:** EC000042 - Miniature circuit breaker (MCB)

**UNSPSC:** 39121603

**eClass:** V11.0 : 27141901

**IDEA Granular Category Code (IGCC):** 4897 >> Miniature circuit breakers

**Object Classification Code:** F

**Standards:** IEC/EN 60898-1  
IEC/EN 60947-2

**Certification Agency:** EN  
IEC

---

---

## Categories

---

Products > Low Voltage Products and Systems > Modular DIN Rail Products > Miniature Circuit Breakers MCBs > Miniature Circuit Breakers MCBs > S200L



  
ABB  
**Eco**  
Solutions™