



 PRODUCT-DETAILS

A95-30-00-36

A95-30-00 190V 50Hz / 220V 60Hz Contactor



General Information

Extended Product Type:	A95-30-00-36
Product ID:	1SFL431001R3600
EAN:	7320500140550
Catalog Description:	A95-30-00 190V 50Hz / 220V 60Hz Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 1000 V. Operated with control voltage, versions from 24V AC, 50 and 60 Hz
Display Name:	A95-30-00-36

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900
Replacement Product ID (NEW):	1SBL407001R1300

Popular Downloads

Data Sheet, Technical Information: 1SBC100192C0206

Instructions and Manuals: 5309660-60

Dimensions

Product Net Width:	90 mm
Product Net Depth / Length:	123.5 mm
Product Net Height:	148 mm
Product Net Weight:	1.8 kg
Dimension Diagram:	53540923-1

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Number of Poles:	3P
Rated Operational Voltage:	Main Circuit 1000 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th} acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 145 A):	
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 145 A (690 V) 55 °C 135 A (690 V) 70 °C 115 A
Rated Operational Current AC-3 (I_e):	(415 V) 55 °C 96 A (440 V) 55 °C 93 A (500 V) 55 °C 80 A (690 V) 55 °C 65 A (1000 V) 55 °C 30 A (380 / 400 V) 55 °C 96 A (220 / 230 / 240 V) 55 °C 96
Rated Operational Current DC-1 (I_e):	(110 V) 2 Poles in Series, 40 °C 145 A (220 V) 3 Poles in Series, 40 °C 145 A
Rated Operational Current DC-3 (I_e):	(110 V) 2 Poles in Series, 40 °C 145 A (220 V) 3 Poles in Series, 40 °C 145 A
Rated Operational Current DC-5 (I_e):	(110 V) 2 Poles in Series, 40 °C 145 A (220 V) 3 Poles in Series, 40 °C 145 A
Rated Operational Power AC-3 (P_e):	(415 V) 55 kW (440 V) 55 kW (500 V) 55 kW (690 V) 55 kW (1000 V) 40 kW (380 / 400 V) 45 kW (220 / 230 / 240 V) 25 kW
Rated Breaking Capacity AC-3:	8 x I_e AC-3
Rated Making Capacity AC-3:	10 x I_e AC-3
Short-Circuit Protective Devices:	gG Type Fuses 160 A

Rated Short-time Withstand Current Low Voltage (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 800 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 160 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 350 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1320 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 500 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 1160 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 800 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Maximum Electrical Switching Frequency:	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability:	10 million
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c):	50 Hz 190 V 60 Hz 220 V
Coil Consumption:	Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A
Power Loss:	at Rated Operating Conditions per Pole 2.7 W
Operate Time:	Between Coil De-energization and NC Contact Closing 7 ... 15 ms Between Coil Energization and NO Contact Closing 10 ... 25 ms
Connecting Capacity Main Circuit:	Bar 30 mm ² Flexible with Cable End 2 x 6 ... 35 mm ² Rigid 2 x 6 ... 65 mm ²
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 1 x 1 ... 4 mm ²
Connecting Capacity:	Bar 30 mm ² Flexible with Cable End 2 x 6 ... 35 mm ² Rigid 2 x 6 ... 65 mm ²
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles:	M8 hexagon socket screw with single connector
Tightening Torque:	Main Circuit 8 N·m
Terminal Type:	Cable Clamp
Product Name:	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
General Use Rating UL/CSA:	(600 V AC) 125 A
Horsepower Rating UL/CSA:	(200 V AC) Three Phase 30 hp (208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 30 hp (440 ... 480 V AC) Three Phase 60 hp (550 ... 600 V AC) Three Phase 75 hp

Full Load Amps Motor Use: (440 ... 480 V AC) Three Phase 77 A
(550 ... 600 V AC) Three Phase 77 A

Environmental

Ambient Air Temperature: Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C
Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C
Close to Contactor for Storage -60 ... +80 °C

Maximum Operating Altitude Permissible: Without Derating 3000 m

Resistance to Shock acc. to IEC 60068-2-27: Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 15 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C1 20 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C2 20 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B1 5 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B2 15 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C1 20 g
Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C2 20 g

Material Compliance

Conflict Minerals Reporting Template (CMRT): 9AKK108467A5658

REACH Declaration: 2CMT2021-006202

RoHS Declaration: 2CMT2021-006277

RoHS Information: Following EU Directive 2011/65/EU

Toxic Substances Control Act - TSCA: 2CMT2023-006525

WEEE B2C / B2B: Business To Business

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

BV Certificate: 07172/D0 BV

CB Certificate: SE-69430

CQC Certificate: CQC2002010304008904
CQC2009010304353526

Declaration of Conformity - CCC: 2020980304001630
2020980304001078

Declaration of Conformity - CE: 2CMT2015-005436

Declaration of Conformity - UKCA: 2CMT2020-006118

DNV Certificate: DNV_E-12191

GL Certificate: GL_99358-97HH

LOVAG Certificate: SE-9645071-1

LR Certificate: LR_12-70027-E1

RINA Certificate: ELE060313XG/001

RMRS Certificate: RMRS_12-03683-315

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	130 mm
Package Level 1 Depth / Length:	265 mm
Package Level 1 Height:	162 mm
Package Level 1 Gross Weight:	2 kg
Package Level 1 EAN:	7320500140550

External Classifications and Standards

Object Classification Code:	Q
ETIM 7:	EC000066 - Power contactor, AC switching
ETIM 8:	EC000066 - Power contactor, AC switching
ETIM 9:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
IDEA Granular Category Code (IGCC):	4755 >> Contactors

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > A Contactors

