

**084Z4022** [↗](#)**Temperature transmitter, MBT 5560, 150 mm, G,1/4**

Temperature range [°C]: -50 - 200, Electrical connection: Angular connector,  
Electrical connection size: Pg 9, Protection tube material: AISI 316 Ti

**PRODUCT DETAILS**

<b>Gross weight</b>	0.179 Kilogram
<b>Net weight</b>	0.131 Kilogram
<b>Volume</b>	0.537 Liter
<b>EAN</b>	5702423211593
<b>Ambient temperature max. [°C]</b>	85 °C
<b>Ambient temperature max. [°F]</b>	185 °F
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Yes exceed limitations
<b>Connection material</b>	AISI 316 Ti
<b>Connection standard</b>	ISO 228
<b>Connection type</b>	G
<b>EEE category</b>	5 small equipment (any external dimension 50 cm)
<b>Electrical conn. Male/Female</b>	Male and Female
<b>Electrical connection</b>	Angular connector
<b>Electrical connection size</b>	Pg 9
<b>Electrical connection standard</b>	EN 175301-803-A
<b>Enclosure rating IP</b>	IP65
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	6(a) 6(b) 6(c) 7(a) 7(c)-I
<b>In scope of WEEE</b>	Yes
<b>In scope of WEEE and contain batteries</b>	No
<b>Insertion length [in]</b>	5.9 in
<b>Insertion length [mm]</b>	150 mm
<b>Insertion type</b>	Fixed
<b>Output signal [mA] [max]</b>	20 mA
<b>Output signal [mA] [min]</b>	4 mA
<b>Packing format</b>	Multi pack
<b>Process connection Male/Female</b>	Male
<b>Process connection material</b>	Stainless steel
<b>Process connection size</b>	1/4
<b>Process connection standard</b>	ISO 228-1-A
<b>Process connection type</b>	G
<b>Product group</b>	Sensors

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Temperature transmitter, MBT 5560, 150 mm, G,1/4**
**PRODUCT DETAILS**

<b>Product Name Description</b>	Temperature transmitter
<b>Protection tube diameter [in]</b>	0.315 in
<b>Protection tube diameter [mm]</b>	8 mm
<b>Protection tube material</b>	AISI 316 Ti
<b>Quantity per packing format</b>	13 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1) Dodecamethylcyclohexasiloxane (D6, CAS no. 540-97-6)
<b>Sensor elem. resistance [Ohm]</b>	1000
<b>Sensor element tolerance</b>	± 1% FS
<b>Sensor element type</b>	Pt
<b>Sensor Insert</b>	Fixed
<b>Supply voltage [V] DC [max]</b>	32 V
<b>Supply voltage [V] DC [max]</b>	32 V
<b>Supply voltage [V] DC [min]</b>	10 V
<b>Supply voltage [V] DC [min]</b>	10 V
<b>Temperature range [°C] [max]</b>	200 °C
<b>Temperature range [°C] [min]</b>	-50 °C
<b>Temperature range [°F] [max]</b>	392 °F
<b>Temperature range [°F] [min]</b>	-58 °F
<b>Transmitter setting range [°C] [max]</b>	100 °C
<b>Transmitter setting range [°C] [min]</b>	0 °C
<b>Transmitter setting range [°F] [max]</b>	212 °F
<b>Transmitter setting range [°F] [min]</b>	32 °F
<b>Transmitter type</b>	Integrated
<b>Type</b>	MBT 5560
<b>Type designation</b>	MBT 5560-0000-0150-10-110
<b>UK RoHS compliance</b>	Yes with exemptions
<b>UK RoHS exemption clause</b>	12 15 18 19 21

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

**Accessories**

**084Z7260 [🔗](#)**
**Sensor pocket, MBT 120**

Protection tube diameter [mm]: 11.0, Insertion length [mm]: 150, Process connection type: G, 1/2,  
Temperature range [°C]: -50 - 200, Protection tube material: AISI 316 Ti, Used for product: MBT  
3560, MBT 5560

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.