


**060L314366**
**Thermostat, KPS79**

Temperature range [°C]: 50 - 100, Reset function: Auto, Contact function: SPDT gold, Sensor type: Remote bulb, Capillary tube length [mm]: 3000, Enclosure rating IP: IP67

**PRODUCT DETAILS**

<b>Gross weight</b>	1.306 Kilogram
<b>Net weight</b>	1.241 Kilogram
<b>Volume</b>	3.684 Liter
<b>EAN</b>	5702423147946
<b>Type</b>	KPS79
<b>Product group</b>	Switches and thermostats
<b>Product Name Description</b>	Thermostat
<b>Amb. Temp. Note</b>	80 °C/176 °F for max 120 min
<b>Ambient temperature range [°C] [max]</b>	70 °C
<b>Ambient temperature range [°C] [min]</b>	-40 °C
<b>Ambient temperature range [°F] [max]</b>	158 °F
<b>Ambient temperature range [°F] [min]</b>	-40 °F
<b>Approval</b>	ABS, BV, CCC, CCS, CE, DNV, EAC, GL, LLC CDC EURO-TYSK, LR, LVD, NKK, RINA, RMRS, RoHS, RoHS China, TYSK, UL
<b>Armoring</b>	Yes
<b>Cap. tube length fraction [in]</b>	118 1/8 in
<b>Capillary tube length [mm]</b>	3000 mm
<b>CE mark</b>	Yes
<b>Charge type</b>	Adsorption
<b>China RoHS compliance</b>	Yes
<b>Connection for pocket or hose</b>	M 18 x 1.5
<b>Contact function</b>	SPDT gold
<b>Contact rating</b>	AC15=4 A, 440 V AC1=10 A, 440 V AC3=6 A, 440 V DC13=12 W, 220 V for gold 1...30mA, 5...30V
<b>Contains batteries</b>	No
<b>Diff. @ Min. range setting [K] [max]</b>	16 K
<b>Diff. @ Min. range setting [K] [min]</b>	4 K
<b>Diff. @ Min. range setting [°C] [max]</b>	16 °C
<b>Diff. @ Min. range setting [°C] [min]</b>	4 °C
<b>Differential type</b>	Adjustable
<b>Electrical conn. comments</b>	Metal cable gland
<b>Electrical conn. Male/Female</b>	Female

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**PRODUCT DETAILS**

<b>Electrical connection</b>	Screwed cable entry
<b>Electrical connection size</b>	Pg 13.5
<b>Electrical connection standard</b>	DIN 40430
<b>Electrical spec. standard</b>	EN 60947-5
<b>EN 60947 electrical properties</b>	Insulation: 400V Pollution degree: 3 Rated impulse voltage: 4 kV Short circuit prot, fuse: 16A
<b>EN 60947 wiring properties</b>	Flex, ferrules: 0.5-1.5 mm <sup>2</sup> Flex, no ferrules: 0.7-2.5 mm <sup>2</sup> Solid/stranded: 0.75-2.5 mm <sup>2</sup>
<b>Enclosure rating IP</b>	IP67
<b>Equipment</b>	Armored cap. tube
<b>EU RoHS compliance</b>	Out of scope
<b>Max. sensor temperature [°C]</b>	200 °C
<b>Max. sensor temperature [°F]</b>	392 °F
<b>Packing format</b>	Multi pack
<b>Product accessories</b>	Switches accessories
<b>Product description</b>	Thermostat
<b>Quantity per packing format</b>	10 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1) Cadmium oxide (CAS no.1306-19-0)
<b>Reset function</b>	Auto
<b>SCIP dossier no.</b>	c1a694ec-501f-43db-83d2-8a9a314459e0
<b>SCIP dossier product name</b>	KP KPS KPU Thermostat
<b>Sensor pocket length min. [in]</b>	3 in
<b>Sensor pocket length min. [mm]</b>	75 mm
<b>Sensor size (Ø x L) [in]</b>	1/2 x 2 1/2 in
<b>Sensor size (Ø x L) [mm]</b>	13 x 63 mm
<b>Sensor type</b>	Remote bulb
<b>Serviceable</b>	No
<b>Temperature range [°C] [max]</b>	100 °C
<b>Temperature range [°C] [min]</b>	50 °C
<b>Temperature range [°F] [max]</b>	212 °F
<b>Temperature range [°F] [min]</b>	122 °F
<b>UL approval file name</b>	E73170
<b>UL mark</b>	Yes

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

**Accessories**


**017-420466** [↗](#)

**Switches accessories, Clamping band**

Type designation: Clamping band, Parts included: 1x screw 4x20, Packing format: Multi pack, Quantity per packing format: 10

**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**060L036666** [🔗](#)

**Switches accessories, Seal kit, For armoured capillary tube**

Type designation: Seal kit, Used for product comments: For armoured capillary tube, Used for product: KPS; RT; CAS; MBC, Packing format: Multi pack, Quantity per packing format: 10



**060L326966** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 160, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10



**060L327066** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 110, Pressure inlet conn. type: NPT, Pressure inlet conn. size [in]: 1/2-14, Packing format: Multi pack, Quantity per packing format: 10



**060L328066** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 110, Pressure inlet conn. type: NPT, Pressure inlet conn. size [in]: 1/2-14, Packing format: Multi pack, Quantity per packing format: 10



**060L340366** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 110, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 3/4, Packing format: Multi pack, Quantity per packing format: 10



**060L320666** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 200, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10



**060L325466** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 250, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 12

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**060L325566** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 330, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 12



**060L326266** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 75, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10



**060L326366** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 160, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10

Image coming soon

**060L326466** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 75, Pressure inlet conn. type: NPT, Pressure inlet conn. size [in]: 1/2-14, Packing format: Multi pack, Quantity per packing format: 10



**060L326666** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 75, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 3/4, Packing format: Multi pack, Quantity per packing format: 10



**060L326766** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 75, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10



**060L326866** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 110, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**060L327166** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 110, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10



**060L328166** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 75, Pressure inlet conn. type: G, Pressure inlet conn. size [in]: 1/2, Packing format: Multi pack, Quantity per packing format: 10



**060L326566** [🔗](#)

**Switches accessories, Sensor pocket**

Type designation: Sensor pocket, Used for product: KPS; RT; CAS; MBC, Sensor pocket length min. [mm]: 65, Pressure inlet conn. type: NPT, Pressure inlet conn. size [in]: 1/2-14, Packing format: Multi pack, Quantity per packing format: 10



**060L327366** [🔗](#)

**Switches accessories, Seal kit, For not arm. capillary tube**

Type designation: Seal kit, Used for product comments: For not arm. capillary tube, Used for product: KPS; RT; CAS; MBC, Packing format: Multi pack, Quantity per packing format: 10

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.