


# Product datasheet

Specifications



## Safety Controller CPU screw term. combined with backplane expansion connector

Local distributor code:  
407168176

XPSMCMCP0802BC

**EAN Code: 3606480992049**

### Main

Range of product	Modicon Safety automation
Device short name	XPSMCM
Electrical connection	Screw terminal
Product or component type	Modular safety controller CPU kit
[Us] rated supply voltage	24 V - 20...20 % DC
Number of inputs	8 digital for input connection 2 digital for interlock start/restart or external device monitoring
Number of outputs	2 safety outputs OSSD for contactor/drive connection 4 test for line control outputs 2 configurable for diagnostic connection
Discrete input voltage	24 V
Discrete output current	400 mA
Discrete input current	400 mA
Discrete input type	PNP Safety input
Discrete output type	PNP
Kit composition	1 safety controller CPU 1 backplane expansion connector
Function of module	Emergency stop conforming to ISO 13850 Guard monitoring conforming to EN/ISO 14119 Enabling switch monitoring conforming to IEC 60947-5-1 Light curtain monitoring conforming to IEC 61496-1 Foot switch monitoring conforming to IEC 60947-5-1 Magnetic switch monitoring conforming to EN/ISO 14119 Two-hand control conforming to EN 574 Safety mat monitoring conforming to EN/ISO 14119 Enabling switch monitoring conforming to IEC 61326-1 Muting function of light curtains conforming to IEC 60947-5-1 Counter functions conforming to IEC 61800-5-2 Speed monitoring conforming to IEC 61800-5-2
Backplane connector	With

### Complementary

Synchronisation time between inputs	< 0.5 ms
Power dissipation in W	3 W
Maximum number of I/O expansion module	14 with 128 discrete output(s) for input 14 with 16 discrete output(s) for output
Integrated connection type	Backplane expansion bus USB 2.0 port
Data storage equipment	SD card (optional)

<b>Inductive load</b>	30 mH
<b>Load capacitance</b>	0.82 µF
<b>Safety level</b>	Can reach category 4 conforming to ISO 13849-1 Can reach PL = e conforming to ISO 13849-1 Type 4 conforming to IEC 61496-1 SILCL 3 conforming to IEC 62061
<b>Quality labels</b>	CE
<b>Local signalling</b>	1 LED green with PWR marking for power ON 1 LED green with RUN marking for RUN (status) 1 LED red with E IN marking for internal error 1 LED red with E EX marking for external error 1 LED orange with COM marking for communication 1 LED blue with EN marking for master enable 8 LEDs yellow with IN marking for input status 2 LEDs green/red with OUT marking for output status 2 LEDs yellow with RST marking for restart signal 2 LEDs yellow with STATUS marking for output channel
<b>Connections - terminals</b>	2 captive screw terminals, removable terminal block 1 captive screw terminals, removable terminal block
<b>Cable cross section</b>	0.2...1.5 mm <sup>2</sup> - AWG 24...AWG 16 flexible cablewithout cable end 0.2...2.5 mm <sup>2</sup> - AWG 24...AWG 14 flexible cablewithout cable end 0.25...1 mm <sup>2</sup> - AWG 23...AWG 18 flexible cablewith cable end, without bezel 0.25...2.5 mm <sup>2</sup> - AWG 23...AWG 14 flexible cablewith cable end, with bezel 0.25...1.5 mm <sup>2</sup> - AWG 23...AWG 16 flexible cablewith cable end, without bezel 0.5...1.5 mm <sup>2</sup> - AWG 20...AWG 16 flexible cablewith cable end, with double bezel 0.2...1 mm <sup>2</sup> - AWG 24...AWG 18 solid cablewithout cable end 0.2...2.5 mm <sup>2</sup> - AWG 24...AWG 14 solid cablewithout cable end
<b>Mounting support</b>	Omega 35 mm DIN rail conforming to EN 50022
<b>Depth</b>	114.5 mm
<b>Height</b>	99 mm
<b>Width</b>	22.5 mm
<b>Product weight</b>	0.26 kg

## Environment

<b>Standards</b>	IEC 61800-5-1 IEC 61496-1 ISO 13849-1 IEC 62061 IEC 61508
<b>Product certifications</b>	RCM cULus TÜV
<b>IP degree of protection</b>	IP20
<b>Ambient air temperature for operation</b>	-10...55 °C
<b>Ambient air temperature for storage</b>	-20...85 °C
<b>Relative humidity</b>	10...95 %
<b>Pollution degree</b>	2
<b>[Uimp] rated impulse withstand voltage</b>	4 kV conforming to IEC 61800-5-1
<b>Safety reliability data</b>	PFHd = 6.06E-9 1/h DC > 99 % MTTFd < 100 years high
<b>Insulation</b>	250 V AC between power supply and housing conforming to IEC 61800-5-1
<b>Overvoltage category</b>	II

<b>Electromagnetic compatibility</b>	Electrostatic discharge immunity test - test level: 6 kV (on contact) conforming to IEC 61000-4-2 Electrostatic discharge immunity test - test level: 20 kV (on air) conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields - test level: 10 V/m (80...1000 MHz) conforming to IEC 61000-4-3 Susceptibility to electromagnetic fields - test level: 30 V/m (1.4 GHz...2 GHz) conforming to IEC 61000-4-3
<b>Vibration resistance</b>	+/-0.35 mm (f= 10...55 Hz) conforming to IEC 61496-1
<b>Shock resistance</b>	10 gn (duration = 16 ms) for 1000 shocks on each axis conforming to IEC 61496-1
<b>service life</b>	20 year(s)

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	4.2 cm
<b>Package 1 Width</b>	12.5 cm
<b>Package 1 Length</b>	16.0 cm
<b>Package 1 Weight</b>	263.0 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	26
<b>Package 2 Height</b>	30.0 cm
<b>Package 2 Width</b>	30.0 cm
<b>Package 2 Length</b>	40.0 cm
<b>Package 2 Weight</b>	7.396 kg

## Logistical informations

<b>Country of origin</b>	IT
--------------------------	----

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>
PVC free	Yes

### Use Longer




#### Lifetime extension

Repair	No
--------	----

### Use Again



#### Repack and remanufacture

Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins