



PRODUCT-DETAILS

CAL5X-11**CAL5X-11 Auxiliary contact block****General Information**

Extended Product Type:	CAL5X-11
Product ID:	1SBN019020R1011
EAN:	6975486359246
Catalog Description:	CAL5X-11 Auxiliary contact block
Long Description:	CAL5X-11 is a 2-pole side mounted auxiliary contact block equipped with screw terminals and can be fitted on AX06...80 ontactors and NX contactor relays. CAL5X auxiliary contact block can be clipped onto the right- and/or left-hand side of the contactors or the contactor relays and bears the corresponding function marking. CAL5X-11 is available with 1 N.O. and 1 N.C. instantaneous contacts for standard industrial environments.
Display Name:	CAL5X-11

Ordering

Minimum Order Quantity:	2 piece
Customs Tariff Number:	85030099

Popular Downloads

EPLAN Data:	9AAC167263_EPLAN
Data Sheet, Technical Information:	1SBC100187L0203
Instructions and Manuals:	1SBB910514D4501
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	12 mm
Product Net Depth / Length:	60 mm
Product Net Height:	74 mm
Product Net Weight:	0.05 kg

Technical

Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Conventional Free-air Thermal Current (I_{th} acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A):	
Rated Operational Current AC-15 (I_e):	(690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I_e):	(24 V) 6 A / 144 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.30 A / 75 W (400 V) 2.8 A / 134 W (500 V) 1 A / 72 W
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 0.1 s 140 A for 1 s 100 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Maximum Electrical Switching Frequency:	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Terminal Type:	Screw Terminals
Suitable For:	AX06 AX09 AX12 AX18 AX25 AX32 AX40 AX50 AX65 AX80 NX

Product Name: Auxiliary Contact Block

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

Environmental Product Declaration - EPD: No Declaration Needed

Certificates and Declarations

CB Certificate:	CB_CN28662
CCC Certificate:	CCC_2013010304656838
CCS Certificate:	CCS_GZ13T00025
CQC Certificate:	CQC2013010304656838
Declaration of Conformity - CCC:	2020980304001061
Declaration of Conformity - CE:	1SBD250013U1000
EAC Certificate:	EAC_RU C-DE ME77 B03562
UL Certificate:	UL-US-L252354-15-61406102-5 UL-CA-L252354-45-61406102-5

Container Information

Package Level 1 Units:	box 2 piece
Package Level 1 Width:	100 mm
Package Level 1 Depth / Length:	106 mm
Package Level 1 Height:	35 mm
Package Level 1 Gross Weight:	0.12 kg
Package Level 1 EAN:	3471522387929

External Classifications and Standards

Object Classification Code:	K
ETIM 7:	EC000041 - Auxiliary contact block

ETIM 8:	EC000041 - Auxiliary contact block
ETIM 9:	EC000041 - Auxiliary contact block
eClass:	V11.0 : 27371302
UNSPSC:	39121522
IDEA Granular Category Code (IGCC):	4743 >> Auxiliary contact block
E-Number (Finland):	3708080

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors

