


PQS819



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/



Product characteristics			
Number of inputs and outputs		Number of digital outputs: 2	
Measuring range		-1...0 bar	-1000...0 mbar -100...0 kPa
Process connection		threaded connection G 1/8 internal thread (2x)	
Application			
Special feature		Gold-plated contacts	
Application		for industrial applications	
Media		compressed air; nitrogen (N2)	
Conditionally suitable for		other media on request	
Medium temperature [°C]		0...60	
Min. burst pressure		30 bar	3 MPa
Pressure rating		10 bar	1 MPa
Vacuum resistance		-1000 mbar	-0.1 MPa
Type of pressure		relative pressure; vacuum	
Electrical data			
Operating voltage [V]		18...30 DC	



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Current consumption	[mA]	< 30
Min. insulation resistance	[MΩ]	100; (500 V DC)
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	0.3
Integrated watchdog		yes

Inputs / outputs

Number of inputs and outputs	Number of digital outputs: 2
------------------------------	------------------------------

Outputs

Total number of outputs	2
Output signal	switching signal; IO-Link; (configurable)
Electrical design	PNP/NPN; (configurable)
Number of digital outputs	2
Output function	normally open / normally closed; (parameterisable)
Max. voltage drop switching output DC	[V] 2.5
Permanent current rating of switching output DC	[mA] 100
Switching frequency DC	[Hz] < 170
Short-circuit protection	yes
Type of short-circuit protection	pulsed
Overload protection	yes

Measuring/setting range

Measuring range	-1...0 bar	-1000...0 mbar	-100...0 kPa
Set point SP	-1...0 bar	-100...0 kPa	
In steps of	0.001 bar	0.1 kPa	0.0001 MPa

Accuracy / deviations

Switch point accuracy	[% of the span] < ± 1
Repeatability	[% of the span] < ± 0,1; (with temperature fluctuations < 10 K:)
Characteristics deviation	[% of the span] < ± 1; (including linearity, hysteresis and repeatability)
Linearity deviation	[% of the span] < ± 1 % (limit value setting to DIN EN IEC 62828-1)
Hysteresis deviation	[% of the span] < ± 0,25
Long-term stability	[% of the span] < ± 0,1; (per year)
Temperature coefficient zero point	[% of the span / 10 K] 0,2
Temperature coefficient span	[% of the span / 10 K] 0,2

Response times

Response time	[ms] 6
---------------	-----------



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Damping process value dAP	[s]	0...4
Damping for the analogue output dAA	[s]	0...99.99

Software / programming

Parameter setting options	display can be rotated and switched off; Teach function; simulation function; diagnostic function
---------------------------	---

Interfaces

Communication interface	IO-Link	
Transmission type	COM3 (230,4 kBaud)	
IO-Link revision	1.1.3	
SDCI standard	IEC 61131-9: 2019-06	
Profiles	Smart Sensor - SSP 4.1.1	Measuring and Switching Sensor, 1 channel
	BLOB	Binary Large Object transfer
	Common - I&D	Identification and Diagnosis
	Extension	Quantity detection, switches when value exceeds the setpoint
	Function	Locator
	Function	ProductURI
SIO mode	yes	
Required master port type	A	
Process data analogue	1	
Process data binary	2	
Min. process cycle time	[ms]	0.6
IO-Link resolution pressure	[bar]	0.0001
IO-Link process data (cyclical)	function	bit length
	pressure	16
	device status	4
	SSC1.1	1
	SSC1.2	1
IO-Link functions (acyclical)	application specific tag; internal temperature; Medium temperature	
Supported DeviceIDs	Type of operation	DeviceID
	default	1745

Operating conditions

Ambient temperature	[°C]	0...60
Storage temperature	[°C]	-25...85
Protection		IP 65

Tests / approvals

EMC	DIN EN 61326-1	
Shock resistance	DIN EN 60068-2-27	50 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	20 g (10...2000 Hz)
MTTF	[years]	508
UL approval	UL approval no.	J065
	File number UL	E174189
Pressure Equipment Directive	Sound engineering practice; can be used for stable gases fluid group 2	

Mechanical data

Weight	[g]	53.05
--------	-----	-------

PQS819



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Housing	rectangular
Dimensions [mm]	37.7 x 30 x 38.6
Materials	PBT; PC; TPE; NBR; FKM; brass; silicon (coated)
Materials (wetted parts)	PBT; FKM; brass; silicon (coated)
Min. pressure cycles	50 million
Process connection	threaded connection G 1/8 internal thread (2x)

Displays / operating elements

Display	Display 1"	128 x 96 pixels
	switching status	2 x LED, yellow
Display unit	mbar; kPa; mmHg; kgf/cm²; %	

Accessories

Items supplied	head cap screw: 2 x (M3 x 8 mm)
----------------	---------------------------------

Remarks


Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M8; coding: A; Contacts: gold-plated



Connection



OUT1	switching output / IO-Link
OUT2	switching output
	colours to DIN EN 60947-5-2
	Core colours
BK=	black
BN=	brown
BU=	blue
WH=	white

PQS819



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Diagrams and graphs

drilling template

