









E3Z-D61 0.5M

Photoelectric sensor, rectangular housing, red LED, diffuse, 100 mm, NPN, Light-ON/Dark-ON, 0.5 m cable

Specifications

Shape	Cuboid
Sensing method	Diffuse reflective
Sensing distance	100 mm
Sensing distance (min.)	5 mm
Setting method	Manual adjustment
Connection method	Cable
Cable length	0.5 m
Output type	NPN
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	PBT
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	20 mm
Type of light	Infrared light
Power supply voltage	12-24 V
Features	Wide beam
Degree of protection (IP)	IP67

Accessories

	E39-L104	Mounting bracket for E3Z sensor, standard, vertical mounting
	E39-L142	Mounting Bracket, protective side wall (for E3Z)
	E39-L144	Sensor mounting Bracket, Protective bracket for E3Z pre-wired
	E39-L153	Mounting bracket for E3Z sensor, L shape, for prewired
	E39-L43	Mounting bracket for E3Z sensor, side mounting
	E39-L98	Protective metal cover for E3S-A/E3Z vertical sensor

Downloads

CAD Library



E3Z
Brochure
EN PDF 1.34 MB



E3Z
Eu declaration of conformity
EN PDF 101 KB



E3Z Compact Photoelectric Sensor with Built-in Amplifier
Datasheet
EN PDF 3.2 MB



E3Z
Instruction Sheet
EN PDF 2.73 MB



IO-Link Series
Brochure
EN PDF 7.95 MB



Sysmac: A Fully Integrated Platform
Brochure
EN PDF 11.9 MB

