



## G3NA-210B-UTU 5-24VDC

Solid state relay, surface mounting, zero crossing, 1-pole, 10 A, 24 to 240 VAC

# Specifications

|  |                |
|--|----------------|
| Application                                    | ON/OFF control |
| Number of phases                               | 1              |
| Mounting method                                | Screw          |
| Terminal type                                  | Screw          |
| LED indicator                                  | ✓              |
| Rated operational voltage, AC                  | 24-240 V       |
| Operating voltage range, AC                    | 19-264 V       |
| Rated operation current I <sub>e</sub> at AC-1 | 10 A           |
| Product Height (unpacked)                      | 58 mm          |
| Product Width (unpacked)                       | 43 mm          |
| Product Depth (unpacked)                       | 27 mm          |
| Supply voltage DC                              | 5-24 V         |
| Control current max.                           | 7 mA           |
| Must operate voltage max.                      | 4 V            |
| Must release voltage min.                      | 1 V            |
| Maximum operating temperature                  | 80 °C          |
| Minimum operating temperature                  | -30 °C         |
| Switching at zero-crossing                     | ✓              |

CAD Library



## G3NA

### Eu declaration of conformity

EN PDF 1.06 MB



## G3NA Solid State Relays Datasheet

EN PDF 2.34 MB



## Industrial Relays Brochure

EN PDF 2.77 MB