



PRODUCT-DETAILS

162LR-C5270

55 LB ELB 4/0STRN .805-1.06 BMETLUG



General Information

Extended Product Type:	162LR-C5270
Product ID:	7TAA121100R0213
EAN:	5415022546408
Catalog Description:	55 LB ELB 4/0STRN .805-1.06 BMETLUG
Long Description:	15kV 200 Amp, Loadbreak Elbow Connector with Test Point, .805 inch - 1.060 Inch Cable Insulation Diameter, 4/0 Stranded Wire Size, Bi-Metal Compression Lug
Display Name:	162LR-C5270

Eco Transparency

Environmental Product Declaration - EPD: 9AKK108470A5449

Ordering

EAN:	5415022546408
UPC:	75114188067

Country of Origin:	United States
Selling Unit of Measure:	each

Container Information

Package Level 1 Units:	1 EA
Package Level 1 Width:	485.648 mm 19.12 in
Package Level 1 Height:	317.5 mm 12.5 in
Package Level 1 Depth / Length:	266.7 mm 10.5 in
Package Level 2 Units:	15 EA
Package Level 2 Width:	0.025 mm 0.001 in
Package Level 2 Height:	0.025 mm 0.001 in
Package Level 2 Depth / Length:	0.025 mm 0.001 in
Package Level 3 Units:	420 EA
Package Level 3 Width:	0 mm 0 in
Package Level 3 Height:	0 mm 0 in
Package Level 3 Depth / Length:	0 mm 0 in

Additional Information

Application:	15kV, 200 Amp
Brand / Label:	Elastimold
Color:	Black
Connection Type:	Push-In
Current Rating:	200 A
Effective Date:	20141025
Environmental Conditions:	All Weatheronditions °C
Includes:	1 Elbow Connector Housing, 1 Compression Lug, 1 Probe, 1 Probe Wrench, 1 Tube of Lubricant, 1 Crimp Chart, V.D. Cap-Peroxide, 1 Installation Instructions sheet.
Insulation Material:	Yes, EPDM Rubber
Material:	Housing - EPDM Rubber
Product Name:	Terminals, electrical splices and electrical couplings
Product Type:	Loadbreak Elbow Connector with Test Point
Size:	7.76 inch (197.1 mm) X 9.03 inch (229.4 mm), 2.92 inch (74.2 mm) Diameter
Special Functions:	15kV, 200 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provision for hot stick operation. Provision for ground wire connection. Wide cable range with minimum number of sizes. Long bi-metal compression lug is standard. Non-corrosive capacitive test point.

Standards:	ANSI/IEEE Standard 386
Temperature Range:	-40 to +65 °C
Voltage Rating:	15 kV

Certificates and Declarations

Data Sheet, Technical Information:	9AKK107045A2438
-------------------------------------------	-----------------

External Classifications and Standards

UNSPSC:	39121421
IDEA Granular Category Code (IGCC):	4586 >> Electrical connector assembly

Material Compliance

RoHS Information:	No declaration needed
WEEE Category:	Product Not in WEEE Scope

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Accessories and Apparatus > Cable Accessories

