



## PRODUCT-DETAILS

**K655LR-J0270****15/25KV 600A DB ELBOW ASSY J0270****General Information**

<b>Extended Product Type:</b>	K655LR-J0270
<b>Product ID:</b>	7TAA122200R0074
<b>EAN:</b>	5415022541571
<b>Catalog Description:</b>	15/25KV 600A DB ELBOW ASSY J0270
<b>Long Description:</b>	600 Amp, 15/25kV, 600 Series Deadbreak, Elbow with Insulated Plug, Cap, Stud, Lug and Cable Adapter. Aluminum Compression Lug. Cable Insulation Diameter 0.980 inch to 1.180 inch. Conductor Size AWG Compressed/Stranded 4/0 or kcmil Compact/Solid 250 or mm2 Compact 125.
<b>Display Name:</b>	K655LR-J0270

**Ordering**

<b>EAN:</b>	5415022541571
<b>UPC:</b>	783786624737
<b>Country of Origin:</b>	United States
<b>Selling Unit of Measure:</b>	each

---

## Container Information

---

<b>Package Level 1 Units:</b>	1 EA
<b>Package Level 1 Width:</b>	298.45 mm 11.75 in
<b>Package Level 1 Height:</b>	114.3 mm 4.5 in
<b>Package Level 1 Depth / Length:</b>	355.6 mm 14 in
<b>Package Level 2 Units:</b>	96 EA
<b>Package Level 2 Width:</b>	0 mm 0 in
<b>Package Level 2 Height:</b>	0 mm 0 in
<b>Package Level 2 Depth / Length:</b>	0 mm 0 in

---



---

## Additional Information

---

<b>Application:</b>	Designed to provide fully shielded, dead-front submersible cable connections to high-voltage apparatus.
<b>Brand / Label:</b>	ELASTIMOLD
<b>Color:</b>	Black
<b>Current Rating:</b>	600 A
<b>Effective Date:</b>	19980115
<b>Environmental Conditions:</b>	Fully Submersible
<b>Includes:</b>	Elbow Connector Housing, Compression Lug, Stud, Insulated Plug with Cap, Lubricant, Cable Adapter, Installation Instructions, Crimp Chart
<b>Insulation Material:</b>	Yes, EPDM Rubber
<b>Material:</b>	Housing - EPDM Rubber
<b>Product Name:</b>	Terminals, electrical splices and electrical couplings
<b>Product Type:</b>	Deadbreak Elbow Connector
<b>Size:</b>	Width 10.36 inch, Length 13.00 inch from Body of T-Body to Center of Bushing.
<b>Special Functions:</b>	Fully shielded, fully submersible molded rubber housing. 100 Percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing as well as adding taps, surge arrestors, and fault current indicators.
<b>Standards:</b>	ANSI/IEEE Standard 386
<b>Temperature Range:</b>	-40 to +65 °C
<b>Voltage Rating:</b>	15 to 25 kV

---



---

## Certificates and Declarations

---

<b>Data Sheet, Technical Information:</b>	9AKK107045A3977
---	-----------------

---

---

### External Classifications and Standards

---

UNSPSC:	39121421
IDEA Granular Category Code (IGCC):	4586 >> Electrical connector assembly

---

---

### Material Compliance

---

RoHS Information:	No declaration needed
WEEE Category:	Product Not in WEEE Scope

---

---

### Categories

---

Products > Low Voltage Products and Systems > Installation Products > Cable Accessories and Apparatus > Cable Accessories

