



# 175G5227 [↗](#)

MCD202055T4CV1  
MCD202055T4CV1  
VLT® Compact Starter MCD 202  
55 kW 100A:4-6: 594  
Three phase, 200-440 VAC  
Control voltage: 24 VAC/VDC  
(B) B-Frame

**Model code:** MCD202055T4CV1

VLT® Compact Starter MCD 200 from Danfoss includes two families of soft starters in the power range 7.5-110 kW. The series offers easy DIN rail mounting for sizes up to 30 kW, 2-wire or 3-wire start/stop control and excellent starting duty (4 x I<sub>e</sub> for 6 seconds). Heavy starting rating at 4x I<sub>e</sub> for 20 seconds. Compatible with grounded delta power systems.

## Product details

Characteristic	Value
Gross weight	4.9 Kilogram
Net weight	4.3 Kilogram
Volume	16.12 Liter
EAN	5702427098664
Product View (Switch)	Global (Standard)
Product Group	VLT® Soft Starter MCD
MCD Series	202
Power Rating	55 kW 100A:4-6: 594
Phase	Three phase
Mains Voltage	200-440 VAC
Control Supply Voltage	24 VAC/VDC
Frame Size	(B) B-Frame
Typecode Part 1	MCD202055T4CV1
Product Catalog	NO VIEW
Modelcode01	MCD202055T4CV1
ECCN EU	Y901
ECCN US	EAR99
Calculated Gross Weight [kg]	4.9

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product details

Characteristic	Value
Calculated Net Weight [kg]	4.3
Plant from Orderline	B901
Vendor	Cannot Determine Vendor
Recommended Factory	Cannot Determine Vendor
Recommended Plant	ERR01

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

## Accessories



[175G9000](#) [↗](#)

**Modbus RTU Module, MCD200, MCD500**

Modbus RTU module (RS485) for MCD 200 and MCD 500



[175G9001](#) [↗](#)

**Profibus Module, MCD200, MCD500**

Profibus option for MCD 200 and MCD 500



[175G9002](#) [↗](#)

**Devicenet module, MCD200, MCD500**



[175G9004](#) [↗](#)

**Remote Operator kit MCD200**

Remote control unit for MCD 200 soft starter.



[175G9009](#) [↗](#)

**USB Module**

USB module for MCD 200 and MCD 500



[175G9905](#) [↗](#)

**Profinet module, MCD200, MCD500**

ProfiNet module

**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



## Accessories



[175G9906](#)

**Ethernet IP module, MCD200, MCD500**

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.