



## H5CC-L8E

Timer, plug-in, 8-pin, DIN 48x48 mm, economy type, No inputs, Contact output (time-limit SPDT + instantaneous SPDT), 100 to 240 VAC supply

# Specifications

|                       |   |
|-----------------------|---|
| Type                  | Digital   |
| Installation type     | DIN rail, On-panel, Socket  |
| Functions             | Multi-functional  |
| Size                  | 1/16 DIN (48 x 48 mm)   |
| Terminal type         | Plug-in   |
| Operating mode        | Flicker OFF Start (Power ON Start), Flicker ON Start (Power ON Start), Interval (Signal Start), ON Delay (Power ON Start) |
| Output type           | Relay   |
| Contact description   | 2 x SPDT  |
| Supply voltage AC     | 100-240 V   |
| Number of pin contact | 8   |
| Features              | Instantaneous contact   |

## Fits to



### **P2CF-08-E**

Socket, DIN rail/surface mounting, 8-pin, screw terminals

# Accessories



**P3G-08**

Socket, back-connecting, 8-pin, screw terminals



**Y92A-48**

Protective cover for DIN48x48mm device, hard plastic (shallow)



**Y92A-48F1**

Protective cover for DIN 48 x 48 mm timer and counter, soft plastic



**Y92A-48G**

Protective cover for DIN48x48mm device



**Y92F-30**

Flush panel mounting adapter for DIN 48x48 mm device



**Y92F-45**

Panel adaptor, 48 x 48 device into 67 x 67 hole

# Downloads

CAD Library



**H5CC**  
Brochure

EN PDF 2.01 MB



**H5CC - Digital Timer**  
Instruction Manual

EN PDF 2.98 MB



**H5CC Digital Timer**  
Datasheet

EN PDF 3.24 MB



**H5CC-AWSD**  
Instruction Manual

EN PDF 2.47 MB

