

# Product datasheet

Specifications



Act: Elect, Float, Mod, 0-10 VDC,  
NSR, 24 VAC, TB, 400 N, Linear,  
SPDT, IP54, FORTA, Globe Valves

8800231030

EAN Code: 7332552013188

## Main

Actuator product range	SpaceLogic
Product or component type	Actuator
Actuator type	Electric
Actuator product series	M400
Actuator model	M400
Product destination	globe valve
Actuator	Linear
Motor type	Brushless DC motor
Control type	Automatic reset
Switch function	2 SPDT
rated supply voltage	24 V AC/DC
Analogue input range	0...10 V DC
Feedback signal	2...10 V DC
Transformer rated power in VA	30 VA
Power consumption in VA	7 VA AC
Hold-in power consumption in W	4 W
Hold-in power consumption in VA	7 VA AC
Power loss return	Non-spring return
Control signal	Floating Proportional/modulating
Stroke length	9...32 mm
Stroke auto calibration	True
Electrical insulation class	Class II
Force N	400 N
Force lbf	90 lbf
Position indicator	Stroke indicator on yoke
Conduit connection	3 x M20 Gland for 6-9 mm O/D cable
Leads and connections	Terminal block
Stroke running time	15 s
IP degree of protection	IP54
Duty cycle	20 %

---

Ambient air temperature for operation	-10...50 °C
Relative humidity	0...90 %
Ambient air temperature for storage	-10...50 °C
Targeted region	Europe Asia Pacific. Australia.

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.8 cm
Package 1 Width	17.8 cm
Package 1 Length	13.6 cm
Package 1 Weight	1.92 kg

---

## Logistical informations

---

Country of origin	LV
-------------------	----

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	221 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	103 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	114 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	4f394b28-50f5-47f5-b920-ba35e4bef3da
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture


Recyclability potential, in %	79
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

