

Product datasheet

Specifications



ClimaSys heating resistance ventil. 250W, 230V aluminium

Local distributor code:

383545457

NSYCR250W230VV

EAN Code: 3606480152436

Main

| | |
|---------------------------|----------------------------|
| Range | ClimaSys |
| Product name | ClimaSys CR |
| Product or component type | Resistance heater with fan |
| Range compatibility | Prisma P Prisma G |
| Power range | 250 W |
| Input voltage | 230 V AC 50/60 Hz |

Complementary

| | |
|---------------------------------------|--|
| Operating position | Vertical |
| Ambient air temperature for operation | -40...70 °C |
| IP degree of protection | IP20 |
| Product certifications | VDE UL cURus |
| Material | Body: extruded aluminium |
| Height | 200 mm |
| Width | 100 mm |
| Depth | 100 mm |
| Condition of use | Air sealed enclosure Heaters must be installed with a thermal controller Electrical protection is needed |
| fixing mode | By clips |
| Mounting support | 35 mm DIN rail |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.000 cm |
| Package 1 Width | 9.000 cm |
| Package 1 Length | 21.500 cm |
| Package 1 Weight | 1.114 kg |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 6 |

| | |
|-------------------------------------|------------|
| Package 2 Height | 16.000 cm |
| Package 2 Width | 33.000 cm |
| Package 2 Length | 48.500 cm |
| Package 2 Weight | 7.640 kg |
| Unit Type of Package 3 | PAM |
| Number of Units in Package 3 | 252 |
| Package 3 Height | 124.000 cm |
| Package 3 Width | 100.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 334.000 kg |

Logistical informations

Country of origin CN

Contractual warranty

Warranty (in months) 18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|------------------|
| Total lifecycle Carbon footprint | 4 441 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 12 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 2 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.1 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 4 426 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 1 kg CO2 eq. |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | 60bb7229-9ac3-41cb-896e-a93aa448ebf8 |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |
| Silicone-free | Yes |

Use Longer




Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|---|
| Recyclability potential, in % | 89 |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |