



---

**PRODUCT-DETAILS**

## 3GBA222210-BDN

### IE4 Super Premium Efficiency Cast Iron Motors, 37 kW, 400 V (3GBA222210-BDN)



---

**General Information**

<b>Product ID:</b>	3GBA222210-BDN
<b>ABB Type Designation:</b>	M2BAX 225SMA 4
<b>Catalog Description:</b>	IE4 Super Premium Efficiency Cast Iron Motors, 37 kW, 400 V (3GBA222210-BDN)
<b>Display Name:</b>	3GBA222210-BDN

---

**Ordering**

<b>ABB Type Designation:</b>	M2BAX 225SMA 4
<b>Invoice Description:</b>	M2BAX 225SMA 4
<b>Product Name:</b>	3-Phase squirrel cage motor
<b>Product Type:</b>	EBA4__M2BAX_CI
<b>Country of Origin:</b>	China
<b>Customs Tariff Number:</b>	85015230
<b>Stocked At (Warehouses):</b>	Menden, Germany

**Medium Description:** 37kW, 4 Poles, Frame Size 225, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GBA222210-BDN)

**Short Description:** 37kW, 4P, Frame Size 225, 3PH, 400V, 50Hz, IP55, IMB5/IM3001

## Electrical

Conn	Temp Class	Network Freq	Network Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	37.00 kW	1483 r/min	39.00 A	0.830	95.20 %	238.00 N-m	9.00
D	--	50 Hz	400 V	37.00 kW	1483 r/min	67.30 A	0.830	95.20 %	239.00 N-m	9.00
Y	--	50 Hz	660 V	37.00 kW	1480 r/min	40.10 A	0.850	95.20 %	239.00 N-m	8.30
D	--	50 Hz	380 V	37.00 kW	1480 r/min	69.70 A	0.850	95.20 %	240.00 N-m	8.20

**Connection Configuration:** D

**Temperature Class Default:** --

**Input Voltage (U<sub>in</sub>):** 400 V

**Frequency (f):** 50 Hz

**Output Power:** 37 kW

**Altitude:** 1000 m

**Ambient Temperature:** 40 °C

**IC Class:** IC411

**IE Class Data (50 Hz):**  
IE Class IE4  
Full Load (100%) 95.2 %  
Partial Load (75%) 95.5 %  
Partial Load (50%) 95.3 %

**IP Class:** IP55

**Insulation Class:** ICLF

**Direction of Rotation:** Both sides

**Number of Poles (High):** 4

**Two Speed Motor:** No

**Type of Duty:** S1

**Voltage Code:** D

## Mechanical

**Frame Material:** Cast Iron

**Frame Size:** 225

**Bearing:** 6313-2Z/C3

**Bearing NDE:** 6213-2Z/C3

**IM Class:** IMB5 IM3001

**Terminator Box Location:** D-End top

---

## Dimensions

---

Product Net Depth / Length:	894 mm
Product Net Height:	558 mm
Product Net Width:	434 mm
Product Net Weight:	363 kg
Gross Weight:	373 kg

---

---

## Environmental

---

WEEE Category:	4. Large Equipment (Any External Dimension More Than 50 cm)
----------------	---

---

---

## External Classifications and Standards

---

UNSPSC:	26101100
---------	----------

---

---

## Categories

---

Products > Motors and Generators > IEC Low Voltage AC Motors > General Performance Motors > IE4 Super Premium Efficiency Cast Iron Motors

