



---

**PRODUCT-DETAILS**

## 3GBP312240-ADM

### IE4 Super Premium Efficiency Cast Iron Motors, 132 kW, 400 V (3GBP312240-ADM)



---

**General Information**

<b>Product ID:</b>	3GBP312240-ADM
<b>ABB Type Designation:</b>	M3BP 315SMD 4
<b>Catalog Description:</b>	IE4 Super Premium Efficiency Cast Iron Motors, 132 kW, 400 V (3GBP312240-ADM)
<b>Display Name:</b>	3GBP312240-ADM

---

**Ordering**

<b>ABB Type Designation:</b>	M3BP 315SMD 4
<b>Invoice Description:</b>	M3BP 315SMD 4
<b>Product Name:</b>	3-Phase squirrel cage motor
<b>Product Type:</b>	3BP4__M3BP_IE4_CI
<b>Country of Origin:</b>	Finland China India Poland
<b>Customs Tariff Number:</b>	85015381

<b>Medium Description:</b>	132kW, 4 Poles, Frame Size 315, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GBP312240-ADM)
<b>Short Description:</b>	132kW, 4P, Frame Size 315, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

## Electrical

Conn	Temp Class	Network Freq	Network Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	132.00 kW	1490 r/min	136.00 A	0.850	96.40 %	846.00 N·m	7.90
D	--	50 Hz	400 V	132.00 kW	1490 r/min	234.00 A	0.850	96.40 %	846.00 N·m	7.90
D	--	50 Hz	415 V	132.00 kW	1491 r/min	231.00 A	0.830	96.40 %	845.00 N·m	8.60
D	--	60 Hz	460 V	132.00 kW	1791 r/min	206.00 A	0.840	96.50 %	704.00 N·m	9.00

<b>Connection Configuration:</b>	D
<b>Temperature Class Default:</b>	--
<b>Input Voltage (U<sub>in</sub>):</b>	400 V
<b>Frequency (f):</b>	50 Hz
<b>Output Power:</b>	132 kW
<b>Altitude:</b>	1000 m
<b>Ambient Temperature:</b>	40 °C
<b>IC Class:</b>	IC411
<b>IE Class Data (50 Hz):</b>	IE Class IE4 Full Load (100%) 96.4 % Partial Load (75%) 96.5 % Partial Load (50%) 96.0 %
<b>IE Class Data (60 Hz):</b>	IE Class IE4 Full Load (100%) 96.5 % Partial Load (75%) 96.3 % Partial Load (50%) 95.6 %
<b>IP Class:</b>	IP55
<b>Insulation Class:</b>	ICLF
<b>Direction of Rotation:</b>	Both sides
<b>Number of Poles (High):</b>	4
<b>Two Speed Motor:</b>	No
<b>Type of Duty:</b>	S1
<b>Voltage Code:</b>	D

## Mechanical

<b>Frame Material:</b>	Cast Iron
<b>Frame Size:</b>	315
<b>Bearing:</b>	6319/C3
<b>Bearing NDE:</b>	6316/C3
<b>IM Class:</b>	IMB3 IM1001

Terminator Box Location: Top

---

---

## Dimensions

---

Product Net Depth / Length: 1202 mm

Product Net Height: 732 mm

Product Net Width: 590 mm

Product Net Weight: 1065 kg

Gross Weight: 1085 kg

---

---

## Environmental

---

WEEE Category: 4. Large Equipment (Any External Dimension More Than 50 cm)

SCIP: 54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland

---

---

## External Classifications and Standards

---

UNSPSC: 26101100

---

---

## Categories

---

Products > Motors and Generators > IEC Low Voltage AC Motors > Process Performance Motors > IE4 Super Premium Efficiency Cast Iron Motors

