



003N2182 [↗](#)

Thermo. operated water valve, AVTA 15, G, 1/2
 Body material: Brass, Opening configuration: Opens on rising sensor temp.,
 Charge type: Universal

Product details

Characteristic	Value
Gross weight	1.642 Kilogram
Net weight	1.242 Kilogram
Volume	4.082 Liter
EAN	5702423023127
Type	AVTA 15
Product group	Water regulating valves
Product Name Description	Thermo. operated water valve
Approval	EAC LLC CDC TYSK PED RoHS RoHS China
Body material	Brass
Cap. tube length fraction [in]	78 3/4 in
Capillary tube gland Int/Ext	Internal
Capillary tube gland size [in]	3/4
Capillary tube gland standard	ISO 228-1
Capillary tube gland type	G
Capillary tube length [mm]	2000 mm
Charge type	Universal
China RoHS compliance	Yes
Connection Internal/External	Internal
Connection size [in]	1/2
Connection standard	ISO 228-1

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Product details

Characteristic	Value
Connection type	G
Contains batteries	No
Cv value [gal/min]	2.2 gal/min
Differential pressure [bar] [max]	10 bar
Differential pressure [bar] [min]	0 bar
Differential pressure [psi] [max]	145 psi
Differential pressure [psi] [min]	0 psi
Equipment	Bracket
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(b) 6(c)
Flow direction indicator	Embossed 1-way arrow
Kv value [m ³ /h]	1.9 m ³ /h
Max. pressure on sensor [bar]	25 bar
Max. pressure on sensor [psig]	362.6 psig
Max. sensor temperature [°C]	125 °C
Max. sensor temperature [°F]	257 °F
Max. test pressure [bar] Pe	25 bar
Max. test pressure [psig]	362.6 psig
Max. Working Pressure [bar]	16 bar
Max. Working Pressure [psig]	232 psig
Media	Neutral media
Medium temperature range [°C] [max]	130 °C
Medium temperature range [°C] [min]	-25 °C
Medium temperature range [°F] [max]	266 °F
Medium temperature range [°F] [min]	-13 °F
Opening configuration	Opens on rising sensor temp.
Orifice size [mm]	15 mm
Orifice size fraction [in]	3/5 in
Packing format	Multi pack
Product accessories	Generic accessories Water valves accessories

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Product details

Characteristic	Value
Quantity per packing format	10 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
SCIP dossier no.	a698bb81-6c39-4d14-a29f-0fc686728af9
SCIP dossier product name	AVTA FJVA
Sensor size (Ø x L) [in]	23/32 x 8 1/4 in
Sensor size (Ø x L) [mm]	18 x 210 mm
Serviceable	Water valve spare parts
Temperature range [°C] [max]	90 °C
Temperature range [°C] [min]	50 °C
Temperature range [°F] [max]	194 °F
Temperature range [°F] [min]	122 °F

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.