

Product datasheet

Specifications



Galaxy VS Maintenance Bypass Panel, single unit, 150kW 400V wallmount

GVSBPSU150KH

Overview

Presentation	Maintenance bypass cabinet for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phases
Product or component type	Panel
Range of product	Galaxy VS
Range compatibility	Galaxy VS

Physical

Height	80 cm
Width	60 cm
Depth	28 cm
Product weight	48 kg

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...3000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-25...55 °C
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49 cm
Package 1 Width	84 cm
Package 1 Length	122 cm
Package 1 Weight	60 kg

Logistical informations

Country of origin	IN
-------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

SCIP Number

5aa5ed58-9f72-49f2-ad76-720ad4129c6e

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture


End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins