

**060G6100****Pressure transmitter, MBS 1700, 0 bar - 6 bar, 0 psi - 87 psi**

Pressure reference: Gauge (relative), Output signal: Current, Electrical connection: Angular connector, Pressure connection type: G, Pressure connection size: 1/4, Specification key: MBS 1700-1811-A1AB04-0

**PRODUCT DETAILS**

<b>Gross weight</b>	0.174 Kilogram
<b>Net weight</b>	0.153 Kilogram
<b>Volume</b>	0.388 Liter
<b>EAN</b>	5702423295340
<b>+ supply</b>	Pin 1
<b>- common</b>	Pin 2
<b>Accuracy, max. [±FS%]</b>	1 %
<b>Accuracy, typical [±FS%]</b>	0.5 %
<b>Adj. zero point and span</b>	No
<b>Ambient temperature range [°C]</b> [max]	85 °C
<b>Ambient temperature range [°C]</b> [min]	-40 °C
<b>Ambient temperature range [°F]</b> [max]	185 °F
<b>Ambient temperature range [°F]</b> [min]	-40 °F
<b>Approval</b>	CE
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Yes
<b>Compensated temp. range [°C]</b> [max]	80 °C
<b>Compensated temp. range [°C]</b> [min]	0 °C
<b>Compensated temp. range [°F]</b> [max]	176 °F
<b>Compensated temp. range [°F]</b> [min]	32 °F
<b>Contain batteries</b>	No
<b>EEE category</b>	5 small equipment (any external dimension < 50 cm)
<b>Electrical conn. Male/Female</b>	Male and Female
<b>Electrical connection</b>	Angular connector
<b>Electrical connection size</b>	Pg 9
<b>Electrical connection standard</b>	EN 175301-803-A
<b>Enclosure rating IP</b>	IP65
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	6(c)
<b>Flush diaphragm</b>	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Pressure transmitter, MBS 1700, 0 bar - 6 bar, 0 psi - 87 psi**
**PRODUCT DETAILS**

<b>High Clipping Level</b>	22.4
<b>In scope of WEEE</b>	Yes
<b>International Article Number</b>	5702423295340
<b>Intrinsically safe</b>	No
<b>Low Clipping level</b>	3.6
<b>Medium temperature range [°C] [max]</b>	85 °C
<b>Medium temperature range [°C] [min]</b>	-40 °C
<b>Medium temperature range [°F] [max]</b>	185 °F
<b>Medium temperature range [°F] [min]</b>	-40 °F
<b>Non-linearity BFSL [±FS%]</b>	0.5 %
<b>Output signal</b>	Current
<b>Output signal [mA] [max]</b>	20 mA
<b>Output signal [mA] [min]</b>	4 mA
<b>Overload pressure max. [bar]</b>	36 bar
<b>Packing format</b>	Multi pack
<b>Pressure connection HEX [mm]</b>	27 mm
<b>Pressure connection size</b>	1/4
<b>Pressure connection standard</b>	EN 837
<b>Pressure connection type</b>	G
<b>Pressure Male/Female</b>	Male
<b>Pressure range [bar] [max]</b>	6 bar
<b>Pressure range [bar] [min]</b>	0 bar
<b>Pressure range [psi] [max]</b>	87 psi
<b>Pressure range [psi] [min]</b>	0 psi
<b>Pressure reference</b>	Gauge (relative)
<b>Product group</b>	Sensors
<b>Product Name Description</b>	Pressure transmitter
<b>Pulse-snobber</b>	No
<b>Quantity per packing format</b>	14 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>Response time max. [ms]</b>	4 ms
<b>SCIP dossier no.</b>	16d2efc6-64f3-4a4e-ae98- a3fd7ce0218d
<b>SCIP dossier product name</b>	AKS/MBS
<b>Specification key</b>	MBS 1700-1811-A1AB04-0
<b>Supply voltage [V] DC [max]</b>	32 V
<b>Supply voltage [V] DC [min]</b>	9 V
<b>Type</b>	MBS 1700
<b>UK RoHS compliance</b>	Yes

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

**For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

---



### **060G0008** [🔗](#)

#### **Accessories, sensors, Plug**

Further information: Knife Contacts, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 96

---



### **060G1034** [🔗](#)

#### **Accessories, sensors, Accessory Plug Connector 5m Cable**

Accessory Plug Connector 5m Cable, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 8

---



### **060G2850** [🔗](#)

#### **Accessory MBD 1000 Display MBT/MBS/AKS**

Accessory MBD 1000 Display MBT/MBS/AKS, Used for product: MBS (4-20mA); MBT5560; MBT 3560; AKS (4-20mA)

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.