


**061B7008** **Test valve, MBV 5000****PRODUCT DETAILS**

<b>Gross weight</b>	2.197 Kilogram
<b>Net weight</b>	1.927 Kilogram
<b>EAN</b>	5702423059034
<b>Type</b>	MBV 5000
<b>Product group</b>	Shut-off and regulating valves
<b>Product Name Description</b>	Test valve
<b>Ambient temperature range [°C] [max]</b>	120 °C
<b>Ambient temperature range [°C] [min]</b>	-20 °C
<b>Ambient temperature range [°F] [max]</b>	248 °F
<b>Ambient temperature range [°F] [min]</b>	-4 °F
<b>Approval</b>	EAC LLC CDC EURO-TYSK RoHS
<b>China RoHS compliance</b>	Out of scope
<b>Contain batteries</b>	No
<b>EU RoHS compliance</b>	Out of scope
<b>MiniMess included</b>	Yes
<b>Number of inputs [pc]</b>	1 pc
<b>Number of outputs [pc]</b>	5 pc
<b>Output connection type</b>	Flange
<b>Packing format</b>	Multi pack
<b>Pressure connection size</b>	1/4
<b>Pressure connection standard</b>	DIN 3852-E
<b>Pressure connection type</b>	G
<b>Pressure Male/Female</b>	Female
<b>Pressure range (Pi) [bar] [max]</b>	120 bar
<b>Pressure range (Pi) [bar] [min]</b>	0 bar
<b>Pressure range (Pi) [bar] oil [max]</b>	180 bar
<b>Pressure range (Pi) [bar] oil [min]</b>	0 bar
<b>Pressure thread conn standard</b>	ISO 228-1
<b>Pulse-snobber</b>	No
<b>Quantity per packing format</b>	6 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>SCIP dossier no.</b>	cd7d33e0- ff13-4f81-9c95-994a26062075

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**PRODUCT DETAILS**

<b>SCIP dossier product name</b>	MBV 1000-5000
<b>Specification key</b>	MBV5000-2511
<b>Test function</b>	Separate
<b>Test pressure connection size</b>	16 x 2
<b>Test pressure connection type</b>	M

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

**For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.