

Specifications

Servo control method	EtherCAT
Drive supply voltage	400 V three phase
Rated output	1.5 kW
Safety functions	SLS, SS1, STO
Product Height (unpacked)	246.4 mm
Product Width (unpacked)	90 mm
Product Depth (unpacked)	236.05 mm
Product Weight (unpacked)	3400 g

Fits to



R88M-1L1K530C-BS2

1S AC servo motor, 1.5 kW, 400 VAC, 3000 rpm, 4.77 Nm, absolute encoder, with brake



R88M-1L1K530C-S2

1S AC servo motor, 1.5 kW, 400 VAC, 3000 rpm, 4.77 Nm, absolute encoder



R88M-1M1K520C-BS2

1S AC servo motor, 1.5 kW, 400 VAC, 2000 rpm, 7.16 Nm, absolute encoder, with brake



R88M-1M1K520C-S2

1S AC servo motor, 1.5 kW, 400 VAC, 2000 rpm, 7.16 Nm, absolute encoder

CAD Library



1S series with SS1/SLS Safety Sub-Functions Brochure

EN PDF 1.8 MB



1S-series servos with SS1/SLS safety functions Users Manual

EN PDF 28 MB



R88D-1SN_-ECT-51 Instruction Sheet

EN PDF 325 KB



R88M-1__R88D-1SN_-ECT-51 AC Servo Drives 1S-series

Datasheet

EN PDF 21.5 MB