

Product datasheet

Specifications



APC Symmetra RM 6kVA Scalable to 6kVA N+1 220-240V

SYH6K6RMI

EAN Code: 3606485318660

Overview

Presentation This parts kit contains spare parts for the APC product model shown.

Main

Main Input Voltage	220 V AC 1 phase 230 V AC 1 phase 240 V AC 1 phase
Cos phi	0.98
Input voltage limits	155...276 V
Number of input connectors	1 hard wire 3-wire
Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	220 V AC 1 phase 230 V AC 1 phase 240 V AC 1 phase
Rated power in W	4200 W
rated power in VA	6000 VA
Output connection type	8 IEC 60320 C13 2 IEC 60320 C19
Bypass type	Internal bypass (automatic and manual)
Crest factor	Up to 5 : 1
Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	6000 VA
Maximum configurable power in W	4200 W
UPS type	On-Line
Wave type	Sine wave
Efficiency	89 % (full load)
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised

Complementary

Battery type	Lead-acid battery
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	1
Number of battery filled slots	3
Number of battery free slots	0
Battery recharge time	4 h

Battery life	3...5 year(s)
Battery charger power	458 W rated
Battery type	Lead-acid internal included
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port Pre-installed network management card 3
Number of rack unit	8U
Number of cables	1
Colour	Black
Height	356 mm
Width	483 mm
Depth	730 mm
Product weight	133.64 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No
Mounting mode	Rack-mounted with included kit
Provided equipment	User manual Rack mounting brackets Rack mounting support rails CD with software
Number of power module	4
Number of power module filled slots	0
Number of power module free slots	0
Number preinstalled power module	3
Additional specification	2kVA power increments
Redundant	Yes
Range of product	Symmetra
Product or component type	Uninterruptible power supply (UPS)
Performance multiplier	1
Value multiplier	1
Size UPS version	Internetworking Server Telecom
Curve equation	Efficiency
Curve fixed loss	0.0532
Curve load maximum	100 %

Curve load minimum	6 %
Curve proportional loss	0.0210
Curve square loss	0.0237
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
UPS size	L

Environment

Product certifications	C-Tick CE IRAM VDE
Standards	EN 50091-2 EN 60950
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	60 dBA
Heat dissipation	1771 Btu/h
Operating altitude	0...10000 ft

General

Number of tare power	225 W
----------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	50.8 cm
Package 1 Width	78.7 cm
Package 1 Length	58.4 cm
Package 1 Weight	148.64 kg

Logistical informations

Country of origin PH

Contractual warranty

Warranty (in months) 24



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	24 262 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 990 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	19 kg CO2 eq.
Carbon footprint of the installation phase [A5]	19 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	22 184 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	50 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	2d54512b-134b-4bf3-ab6e-849ecf1e3919
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

