



 PRODUCT-DETAILS

A2N 250 TMF 200-2000 3p F F

A2N 250 TMF 200-2000 3p F F



General Information

Extended Product Type:	A2N 250 TMF 200-2000 3p F F
Product ID:	1SDA066784R1
EAN:	8015644006945
Catalog Description:	A2N 250 TMF 200-2000 3p F F
Long Description:	C.BREAKER FORMULA A2N 250 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 200-2000 A
Display Name:	A2N 250 TMF 200-2000 3p F F

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
Toxic Substances Control Act - TSCA:	9AKK108467A8326
SCIP:	cb2db7cc-f1d3-4c44-8411-9ebcaab89643 Italy

Simplified SCIP:	1fe706d0-4e12-4bca-bf3a-522b4e52d783 Germany 5445f7e3-f820-4a0d-8c1d-03be09fad0a6 Bulgaria e8641ddc-4ec0-47d7-866d-5bbfcbde6e33 Germany 7d57fea0-0399-4949-ba36-bba0126a8cbc Denmark 6f7ef39f-a454-4792-a5b9-0a815273dd6b Norway f70a53d5-1c5e-4774-a55a-1c5d10344652 Poland a1d8fa3c-2a6b-4843-a3cc-83eebcece0e2 Sweden 5950c618-79b2-436a-900b-6ef69ee29395 Poland 1ac775b8-8a02-4b87-b4c8-021f752af328 France e04f0605-aff0-4ec4-8d35-352a817b0906 Finland 19eef35b-3f94-42b6-9cb2-b14acbc05c8b Sweden 7f17b5b8-7cfe-4a0e-bb0f-7ab35324f228 Croatia 14e23a44-89e9-45ef-8a53-18d6ecd23619 Belgium c6ca9851-9ffa-41ab-bfaf-bf9f200a8e37 Spain f4881ff9-8e55-4225-bd33-39b3254738e Hungary bff4f2ef-1942-4658-a859-ef07bbcc972e Netherlands e7c608a0-1606-44cf-95cf-8a368fac01b8 Germany aa2bbc0b-a7b6-47aa-a67f-f353334db318 France 9cfd98a3-3b53-448e-9186-13be7aef799 Germany d5aaa5e3-07f9-423b-8f32-404b81bcbf03 Germany 99f2f6a9-67c5-4822-aa1d-69f205c44e23 Poland 247fff04-9119-4bd5-a3ab-63adac49a23f Czechia 5a8a93ca-ee03-4449-b9c5-810afe5fef89 Belgium 2076f0a3-ef75-40c6-93db-6ff948d6d76d Estonia 4a92a727-97e4-45f5-b9ae-440c2b7d45b0 Hungary 43b408fa-6be0-4b08-8c2f-8f2d49a51008 Greece aa560844-6397-4945-bd27-534c50cea1e0 Portugal
-------------------------	---

Environmental

Environmental Information:	1SDL000183R0001 9AKK108467A6707
-----------------------------------	------------------------------------

Ordering

Order Code US and Canada:	ABN200TW
EAN:	8015644006945
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	105 mm
Product Net Height:	150 mm
Product Net Depth / Length:	60 mm
Product Net Weight:	1.396 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	162 mm
Package Level 1 Height:	120 mm

Package Level 1 Depth / Length:	155 mm
Package Level 1 Gross Weight:	1.45 kg
Package Level 1 EAN:	8015644006945

Additional Information

Product Main Type:	SACE FORMULA
Product Name:	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker
Version:	F

Technical

Electrical Durability:	4000 cycle
Mechanical Durability:	10000 cycle
Number of Poles:	3P
Opening Time:	CB with SOR 15 ms CB with UVR 15 ms
Power Loss:	at Rated Operating Conditions per Pole 12 W
Rated Current (I_n):	Main Circuit 200 A
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	690 V
Rated Operational Voltage:	550 V AC 250 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(240 V AC) 42.5 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 12.5 kA (480 V AC) 12.5 kA (500 V AC) 5 kA (250 V DC) 2 Poles in Series 18 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(240 V AC) 85 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 25 kA (480 V AC) 25 kA (500 V AC) 10 kA (250 V DC) 2 Poles in Series 36 kA
Rated Uninterrupted Current (I_u):	250 A
Release:	TMF
Release Type:	TM
Short-Circuit Performance Level:	N
Standards:	IEC
Sub-type:	A2
Terminal Connection Type:	Front

Certificates and Declarations

Data Sheet, Technical Information:	1SDC210032D0204
Declaration of Conformity - CE:	9AKK106713A5518
Wiring Diagram:	1SDM000067R0001
Instructions and Manuals:	1SDH000718R0001

External Classifications and Standards

ETIM 9:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code:	Q
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
eClass:	V11.1 : 27370409

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Moulded Case Circuit Breakers > Formula DSA

