

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7064-5AK74-1MH2



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	6,000 rpm
Number of poles	10
Rated torque (100 K)	2.9 Nm
Rated current	3.40 A
Static torque (60 K)	7.7 Nm
Static torque (100 K)	9.0 Nm
Stall current (60 K)	7.70 A
Stall current (100 K)	9.00 A
Rotor moment of inertia	14.70 kgcm <sup>2</sup>
Efficiency	91.0 %

### Physical constants

Torque constant	1.00 Nm/A
Voltage constant at 20° C	64.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.39 Ω
Rotary field inductance	4.1 mH
Electrical time constant	11.00 ms
Mechanical time constant	1.40 ms
Thermal time constant	30 min
Shaft torsional stiffness	26,000 Nm/rad
Net weight of the motor	11.4 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP67
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface
Electrical connection	Connector turnable
Connector size	1

### Optimum operating point

Optimum speed	4,500 rpm
Optimum power	2.6 kW

### Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	8,000 rpm
Maximum torque	36.0 Nm
Maximum current	45.00 A

### Recommended Motor Module

Rated inverter current	9.00 A
Maximum inverter current	27.00 A
Maximum torque	25.3 Nm

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	18.0 Nm
Braking torque	11.0 Nm
Power supply voltage	DC 24 V
Coil current	0.80 A
Permissible brake work	880 J
Opening time	150 ms
Closing time	50 ms