





---

 PRODUCT-DETAILS

## BER16-4KF

# BER16-4KF Connection Set for Reversing Contactors




---

### General Information

<b>Extended Product Type:</b>	BER16-4KF
<b>Product ID:</b>	1SBN081322R1000
<b>EAN:</b>	3471523131422
<b>Catalog Description:</b>	BER16-4KF Connection Set for Reversing Contactors
<b>Long Description:</b>	<p>BER16-4KF is a connection set used to connect the main poles of two 3-pole AF09..K ... AF16..K, AFC09..K ... AFC16..K contactors mounted side by side.</p> <p>The connection sets are made up of:</p> <ul style="list-style-type: none"> <li>• 1 upstream and 1 downstream connections</li> <li>• Insulated, solid copper bars</li> <li>• Black fork pieces for a quick dismounting of reversing contactors.</li> </ul> <p>With the Push-in Spring terminals, one push is all you need for a faster than ever installation, an easier than ever wiring and a reliable as ever connection.</p>
<b>Display Name:</b>	BER16-4KF

---

### Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85389099

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SBC100214C0202
<b>Instructions and Manuals:</b>	1SBC101056M6801
<b>Instructions and Manuals (Part 2):</b>	1SAC200017M0002
<b>CAD Dimensional Drawing:</b>	2CDC001079B0201

## Dimensions

<b>Product Net Width:</b>	72 mm
<b>Product Net Depth / Length:</b>	27 mm
<b>Product Net Height:</b>	32 mm
<b>Product Net Weight:</b>	0.05 kg

## Technical

<b>Standards:</b>	EN 60947-1, EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1
<b>Rated Operational Voltage:</b>	Main Circuit 690 V AC
<b>Rated Frequency (f):</b>	Main Circuit 50 / 60 Hz
<b>Terminal Type:</b>	Push-in Spring Terminals
<b>Suitable For:</b>	AF09 AF09Z AF12 AF12Z AF16 AF16Z
<b>Product Name:</b>	Connection Set

## Material Compliance

<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108467A5658
<b>REACH Declaration:</b>	2CMT2021-006202
<b>RoHS Declaration:</b>	2CMT2021-006277
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
<b>Toxic Substances Control Act - TSCA:</b>	2CMT2023-006525
<b>WEEE B2C / B2B:</b>	Business To Business
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)

## Certificates and Declarations

<b>Declaration of Conformity - CE:</b>	1SBD250021U1000
<b>Declaration of Conformity - UKCA:</b>	1SBD250043U1000

UL Certificate: UL-US-L312527-151-12119002-9  
UL-CA-L312527-451-12119002-8

---

## Container Information

---

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	36 mm
Package Level 1 Depth / Length:	75 mm
Package Level 1 Height:	35 mm
Package Level 1 Gross Weight:	0.06 kg
Package Level 1 EAN:	3471523131422

---

---

## External Classifications and Standards

---

ETIM 7:	EC002498 - Accessories for low-voltage switch technology
ETIM 8:	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 9:	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass:	V11.0 : 27371392
UNSPSC:	39120000
E-Number (Finland):	3709748
E-Number (Sweden):	3210699

---

---

## Categories

---

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors

