




PRODUCT-DETAILS

TB541-ETH

Terminal base. For AC500 V2. 4 slots for communication module. Ethernet interface. 2 serial interfaces RS232/RS485 (TB541-ETH)



General Information

| | |
|-------------------------------|--|
| Extended Product Type: | TB541-ETH |
| Product ID: | 1SAP114100R0270 |
| ABB Type Designation: | TB541-ETH |
| EAN: | 4016779711487 |
| Catalog Description: | Terminal base. For AC500 V2. 4 slots for communication module. Ethernet interface. 2 serial interfaces RS232/RS485 (TB541-ETH) |
| Long Description: | TB541-ETH: AC500 Terminal base. For AC500 V2. 4 slots for communication module. Ethernet interface. 2 serial interfaces RS232/RS485. |
| Display Name: | TB541-ETH |

Ordering

| | |
|-----------------------------|--|
| CN8: | 85389091 |
| Invoice Description: | Terminal base. For AC500 V2. 4 slots for communication module. Ethernet interface. 2 serial interfaces RS232/RS485 (TB541-ETH) |

| | |
|---------------------------------|---------|
| Made To Order: | No |
| Minimum Order Quantity: | 1 piece |
| Order Multiple: | 1 piece |
| Selling Unit of Measure: | piece |

Dimensions

| | |
|--|----------------|
| Product Net Weight: | 0.24 kg |
| Product Net Depth / Length: | 28 mm |
| Product Net Height: | 135 mm |
| Product Net Width: | 179.5 mm |
| Gross Weight: | 0.311 kg |
| Package Level 1 Depth / Length: | 147 mm |
| Package Level 1 Height: | 40 mm |
| Package Level 1 Width: | 189 mm |
| Package Level 1 Units: | carton 1 piece |

Certificates and Declarations

| | |
|--|--|
| Declaration of Conformity - CE: | 3ADR980140 |
| REACH Date: | 20241206 |
| REACH Declaration: | 3ADR980139 |
| REACH Information: | True - contains substances > 0.1 mass percentage |
| SCIP: | 0af38f44-ebb9-41bc-85b8-14a405e35442 Germany |
| RoHS Declaration: | 3ADR980140 |
| RoHS Information: | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Technical

| | |
|---------------------------------|---|
| Function: | For AC500 V2. 4 slots for communication module. Ethernet interface. 2 serial interfaces RS232/RS485 |
| Communication Interface: | D-SUB/RJ45/Terminals |
| Input Voltage Type: | DC |
| Degree of Protection: | IP20 |
| Supply Voltage: | 24 V DC |
| Ambient Air Temperature: | Operation 0 ... +60 °C Storage -40 ... +70 °C |

Additional Information

| | |
|---------------------------|-----------------------------|
| Product Main Type: | TB541 |
| Product Name: | Distributed Automation PLCs |

External Classifications and Standards

| | |
|-----------------|------------------------------|
| eClass: | 27-24-22-92 |
| ETIM 8: | EC000810 - PLC mounting rack |
| ETIM 9: | EC000810 - PLC mounting rack |
| ETIM 10: | EC000810 - PLC mounting rack |
| UNSPSC: | 32151703 |

Environmental

| | |
|------------------------|--|
| WEEE B2C / B2B: | Business To Business |
| WEEE Category: | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Products > PLC Automation > Programmable Logic Controllers PLCs > AC500 > CPUs

