



## E3FB-LP22-F2

Photoelectric sensor, M18 threaded barrel, metal, red LED, background suppression, 200 mm, PNP, Light-ON/Dark-ON, inverted logic, M12 connector

# Specifications

Shape	Cylindrical axial
Sensing method	Background suppression
Sensing distance	200 mm
Setting method	Fixed
Connection method	Connector M12
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	0.5 ms
Material housing	Brass, nickel plated
Thread size	M18
Product Length (unpacked)	48 mm
Type of light	Polarity free red light
Power supply voltage	10-30 V
Degree of protection (IP)	IP67/IP69K

# Accessories



**E39-L183**

M18 L-type mounting bracket, stainless steel (SUS304)

# Related products



## M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

# Downloads

CAD Library



### E3FA Cylindrical Photoelectric Sensors Brochure

EN PDF 9.13 MB



### E3FA/B-F2 Photoelectric Sensors Datasheet

EN PDF 1.6 MB



### E3FB-\_\_\_\_\_ Instruction Manual

EN PDF 351 KB

#### TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 6 May, 2026. Click here for [terms of use](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU