



PYF14-ESS-B

Socket, with coil terminals on the bottom and with the common and NC & NO terminals on the top - Black.

Specifications

Applicable product family	MY2K, MY4, MY4-GS
Mounting method	DIN rail/screw
Terminal type	Rise-up
Product Width (unpacked)	27 mm
Product Height (unpacked)	83 mm
Product Depth (unpacked)	61 mm
Color	Black
Hold down clip included	×
Release Lever included	×
Applicable ferrules	Forked terminals, Round terminals

Fits to



MY4-GS-R AC110/120

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 100/110 VAC



MY4-GS-R AC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC



MY4-GS-R AC220/240

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC



MY4-GS-R AC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC

**MY4-GS-R AC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VAC

**MY4-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC

**MY4-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

**MY4-GS-R DC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC

**MY4H 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

**MY4H 12VDC**

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

**MY4H 24VAC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VAC

**MY4H 24VDC**

Relay, plug-in, 14-pin, 4PDT, 1 A, hermetically-sealed

**MY4IN-CR-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 110/120 VAC

**MY4IN-CR-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 220/240 VAC

**MY4IN-D2-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

**MY4IN-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC.

**MY4IN-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY4IN-GS-R AC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY4IN-GS-R DC100/110**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY4IN-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VDC



MY4IN-GS-R DC24
Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VDC



MY4IN-GS-R DC48
Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VDC



MY4Z 110/120VAC (S)
Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 100/120 VAC



MY4Z 220/240VAC (S)
Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 220/240 VAC



MY4Z 24VDC (S)
Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 24 VDC



MY4ZH 100/110VAC
Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts, 110 VAC



MY4ZH 24VDC
Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts



MY4ZIN 220/240VAC (S)
Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 220/240 VDC



MY4ZIN 24VAC (S)
Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 24 VAC



MY4ZIN 24VDC (S)
Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZIN-D2 24VDC (S)
Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC



MY4ZN 110/120VAC (S)
Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 110/120 VAC



MY4ZN 220/240VAC (S)
Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 220/240 VAC



MY4ZN 24VAC (S)
Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 24 VAC



MY4ZN 24VDC (S)
Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 24 VDC



MY4ZN 48/50VAC (S)
Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 48/50 VAC



**MY4ZN-CR
110/120VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, RC circuit, 110/120 VAC



**MY4ZN-CR
220/240VAC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, RC circuit, 220/240 VAC



**MY4ZN-D2
100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 100/110 VDC



MY4ZN-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 24 VDC



MY4ZN-D2 48VDC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, diode, 48 VDC



MY4ZN1-D2 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, diode, 24 VDC



MYQ4 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 110/120 VAC



MYQ4 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 220/240 VAC



MYQ4 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 24 VDC



MYQ4N 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 110/120 VAC



MYQ4N 220/240VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 220/240 VAC



MYQ4N 24VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VAC



MYQ4N 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 24 VDC



MYQ4Z 200/220VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, bifurcated contacts

Accessories



PYC-0

Metal retaining clip (wire sprig clip) for use with PYF14-ESN/ESS (for use with relays only)



PYC-35-B

Plastic release lever for PYF14-ESS-B/-ES-B



PYC-TR

Labels for P2RF-05/08-ESS socket

Downloads

CAD Library



PYF14-ESS-B Relay Sockets

Datasheet

EN PDF 545 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 14 May, 2026. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU