



PRODUCT-DETAILS

SN201 L-C16-L

Miniature circuit breaker - SN201L - N Left -
1P+N - 16 A - C - (230 V) 4.5 kA



General Information

Extended Product Type:	SN201 L-C16-L
Product ID:	2CSS245102R0164
EAN:	8012542085751
Catalog Description:	Miniature circuit breaker - SN201L - N Left - 1P+N - 16 A - C - (230 V) 4.5 kA
Long Description:	The SN201 series miniature circuit breaker is a 1P+N device in 1 module for the protection of circuits against overload and short circuit. Neutral is on the left
Display Name:	SN201 L-C16-L

ABB EcoSolutions

EcoSolutions Profile:	9AKK108471A1004
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 90.63 %
Sustainable Material Content in Packaging (wt. %):	Recycled Paper - 00 % Recycled Cardboard - 79 %
Extended Product Lifetime:	Product Durability

End Of Life Disassembling Instructions: 9AKK108469A7476

Environmental Product Declaration - EPD: 9AKK108469A9820

Technical

Dielectric Test Voltage:	50 / 60 Hz - 1 min 2 kV
Primary Rated Impulse Withstand Voltage:	4 kV
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(230 V) 6 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(230 V AC) 4.5 kA
Power Supply Connection:	Arbitrary
Contact Position Indication:	ON / OFF
Energy Limiting Class:	3
Electrical Endurance:	10000 cycle
Mechanical Endurance:	20000 cycle
Number of Protected Poles:	1
Number of Poles:	1P+N
Number of Modular Spacings per DIN Rail:	1
Position of Neutral Terminals:	Left
Tightening Torque:	1.2 N·m
Actuator Type:	Toggle
Screw Terminal Type:	Cage Terminal
Accessories Available:	Yes
Connecting Capacity:	Flexible 1 ... 10 mm ² Rigid 1 ... 16 mm ²
Wire Stripping Length:	11 mm
Terminal Type:	Screw Terminals

Electrical

Tripping Characteristic:	C
Rated Voltage (U_r):	230 V AC
Rated Operational Voltage:	acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U_i):	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U_{imp}):	4 kV
Input Voltage Type:	AC
Rated Current (I_n):	16 A
Rated Short-Circuit Capacity:	(230 V) 4.5 kA
Rated Frequency (f):	50 / 60 Hz
Power Loss:	Total 3.6 W
Overvoltage Category:	III

Design

Housing Material: Insulation group II, RAL 7035

Material Compliance

RoHS Declaration: 9AKK106713A5572

RoHS Information: Following EU Directive 2011/65/EU

RoHS Date: 20190722

Conflict Minerals Reporting Template (CMRT): 9AKK108468A3363

SCIP: 60ddb6a7-cab4-4601-bf11-c2da4a87ceb9 Italy

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B: Business To Consumer

Environmental

Ambient Air Temperature: Operation -25 ... +55 °C

Reference Ambient Air Temperature: 30 °C

Degree of Protection: IP20

Pollution Degree: 2

Environmental Conditions: 28 cycles
;with 55 °C / 90-96 %
;and 25 °C / 95-100 %

Resistance to Vibrations: 20 Cycles with Load 0.8 In: 5g or 0.35mm 5 ... 150 ... 5 Hz

Resistance to Shock acc. to IEC 60068-2-27: 30g 2 shocks 13 ms

Environmental Information: refer to RoHS information

Dimensions

Width in Number of Modular Spacings: 1

Product Net Width: 18 mm

Product Net Height: 85 mm

Product Net Depth / Length: 69 mm

Product Net Weight: 110 g

Built-In Depth (t₂): 69 mm

Ordering

Package Level 1 Units: box 6 piece

Package Level 1 Gross Weight: 0.684 kg

Certificates and Declarations

Declaration of Conformity - CE: 9AKK106713A5572

Installation

Instructions and Manuals: No document needed

Mounting Position: Any

Popular Downloads

Data Sheet, Technical Information: 2CSC400002D0209

External Classifications and Standards

ETIM 9: EC000042 - Miniature circuit breaker (MCB)

ETIM 10: EC000042 - Miniature circuit breaker (MCB)

UNSPSC: 39121603

eClass: V11.0 : 27141901

Object Classification Code: F

Standards: IEC/EN 60898-1

Categories

Products > Low Voltage Products and Systems > Modular DIN Rail Products > Miniature Circuit Breakers MCBs > Miniature Circuit Breakers MCBs > SN201 L - N Left

Products > Low Voltage Products and Systems > Modular DIN Rail Products > Miniature Circuit Breakers MCBs > Miniature Circuit Breakers MCBs > SN201L



