

Product datasheet

Specifications



"PanelSet S3X stainless 316L, Scotch Brite® finish, H300xW200xD150 mm."

Local distributor code:

398252609

NSYS3X3215H

EAN Code: 3606480155062

Main

| | |
|----------------------|----------------------------------|
| Range | Spacial |
| Product name | Spacial S3X |
| enclosure type | Multi-purpose |
| category | Compact enclosure |
| nominal height | 300 mm |
| nominal width | 200 mm |
| nominal depth | 150 mm |
| product installation | Wall-mounting |
| Device composition | 1 body 1 lock: door 1 door |

Complementary

| | |
|-----------------------------|--|
| Body type | Single piece body, cross-shaped structure Gutter shaped front rail |
| Door type | Plain |
| Number of doors | Front face: 1 door(s) |
| Door opening side | Reversible (120 °) |
| Lock type | 3 mm double-bar lock |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Without gland plate |
| Accessibility for operation | Front |
| Removable parts | Door by hinges |
| Material | Lock: zamak Hinge: stainless steel Body and door: stainless steel 316L |
| Surface finish | Body and door: Scotch-Brite® brushed Lock: chromium plated |
| Product weight | 3.12 kg |

Environment

| | |
|------------------------|-----------------------------|
| Standards | IEC 62208 UL CUL |
| Product certifications | UL 508 type A CAN/CSA 22 |

| | |
|-------------------------------------|-------------------------------|
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |
| Environmental characteristic | Corrosive Specific hygiene |

Packing Units

| | |
|-------------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.000 cm |
| Package 1 Width | 21.500 cm |
| Package 1 Length | 32.000 cm |
| Package 1 Weight | 3.120 kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 24 |
| Package 2 Height | 48.000 cm |
| Package 2 Width | 100.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 90.300 kg |

Logistical informations

| | |
|--------------------------|----|
| Country of origin | BG |
|--------------------------|----|

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 46 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 32 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 6 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.2 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 8 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | E893f0a0-d2cc-4011-9425-3873dde70142 |
| EU RoHS Directive | Compliant |
| REACH Regulation | Free of Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|--|
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features

High resistance to corrosion

Earthing studs included

Large choice of dimensions & accessories

Built to last

Easy to equip
Easy to maintain

Easy & quick assembly