

# Product datasheet

Specifications

## W600 ADJUSTABLE MOD. DEV. RAIL PRISMA G



LVS03002

EAN Code: 3606481875426

### Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G
Type of rail	Modular Adjustable
Installed device	TeSys: fixed GV2L TeSys: fixed GV2P TeSys: fixed GV3 ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles description	9 x 3P: fixed GV2L 9 x 3P: fixed GV2P 7 x 3P: fixed GV3 1 x 3P: fixed NG160 1 x 4P: fixed NG160 1 x 3P: fixed NG160 NA 1 x 4P: fixed NG160 NA 1 x 3P or 4P: fixed NSXm vertical installation

### Complementary

installation description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
--------------------------	--

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Number of vertical modules [50 mm]</b>	3 module(s): GV2L, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2L, direct in 600 mm Widewall-mounted enclosure 3 module(s): GV2P, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2P, direct in 600 mm Widewall-mounted enclosure 5 module(s): GV3, direct in 600 mm Widefloor-standing enclosure 5 module(s): GV3, direct in 600 mm Widewall-mounted enclosure 5 module(s): NG160 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure 5 module(s): NG160 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure 5 module(s): NG160 NA without earth leakage protection , direct in 600 mm Widefloor-standing enclosure 5 module(s): NG160 NA without earth leakage protection , direct in 600 mm Widewall-mounted enclosure 7 module(s): NSXm without earth leakage protection , direct in 600 mm Widefloor-standing enclosure 7 module(s): NSXm without earth leakage protection , direct in 600 mm Widewall-mounted enclosure 7 module(s): NSXm without earth leakage protection , connection block in 600 mm Widefloor-standing enclosure 7 module(s): NSXm without earth leakage protection , connection block in 600 mm Widewall-mounted enclosure 5 module(s): NG160 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure 5 module(s): NG160 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure 7 module(s): NSXm with earth leakage protection , direct in 600 mm Widefloor-standing enclosure 7 module(s): NSXm with earth leakage protection , direct in 600 mm Widewall-mounted enclosure 7 module(s): NSXm with earth leakage protection , connection block in 600 mm Widefloor-standing enclosure 7 module(s): NSXm with earth leakage protection , connection block in 600 mm Widewall-mounted enclosure
---	--

<b>9 mm pitches</b>	48
<b>Quantity per set</b>	Set of 1
<b>Height</b>	58 mm
<b>Width</b>	467 mm
<b>Depth</b>	97 mm
<b>Product weight</b>	0.34 kg
<b>Colour</b>	Natural
<b>Material</b>	Metal

## Environment

<b>Standards</b>	IEC 61439-2 IEC 61439-1
<b>Product certifications</b>	ASTA

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	10.500 cm
<b>Package 1 Width</b>	5.700 cm
<b>Package 1 Length</b>	46.800 cm
<b>Package 1 Weight</b>	311.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	15.500 cm

Package 2 Width	31.000 cm
Package 2 Length	49.000 cm
Package 2 Weight	3.540 kg
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Height	104.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	107.300 kg

## Logistical informations

Country of origin	FR
-------------------	----

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No

Technical Illustration

Dimensions

---



- All dimensions are approximate and are in  
- Also see technical documentation.