

Product datasheet

Specifications



Device monitoring and management, Network Management Cards, NMC3, secure remote UPS monitoring and management

AP9640

Main

Range of product	Network Management Cards
Range compatibility	Galaxy VM Galaxy VX Symmetra PX Easy UPS 3M Advanced Easy UPS 3-Phase Modular Galaxy PX Galaxy 3L Pro Smart-UPS Smart-UPS Ultra Smart-UPS Online Smart-UPS Modular Ultra Smart-UPS Battery Systems Back-UPS SX3 Refurbished Smart-UPS
Product or component type	Device monitoring and management
Provided equipment	Micro-USB cable Installation manual
Number of input phases	1 3
Standards	EN 55024 BS EN 55024 EN 61000-4-2 BS EN 61000-4-2 EN 61000-4-3 BS EN 61000-4-3 EN 61000-4-4 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 EN 61000-4-6 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 EN 55035 BS EN 55035 EN 62040-2 BS EN 62040-2 EN 61326-2 BS EN 61326-2 ICES-003 class A VCCI class A EN 61000-6-3 BS EN 61000-6-3 EN 55032: class A BS EN 55032: class A

Physical

Product weight	0.08 kg
Width	12.1 cm

Height	3.8 cm
Depth	11.4 cm

Conformance

Product certifications	FCC Class A AS/NZS AS/NZS 3548 (C-Tick) class A FCC part 15 class A GOST UK PSTI
------------------------	---

Environmental

Storage Relative Humidity	0...95 %
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Ambient air temperature for operation	-5...45 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft

Communications & Management

Communication network type	10/100/1000BASE-T
Authentication	Radius Lightweight Directory Access Protocol (LDAP)
Communication port protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	15.9 cm
Package 1 Length	23.5 cm
Package 1 Weight	0.34 kg

Logistical informations

Country of origin	IN
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	110 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	106 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	End of Life Information
Removable battery	Yes
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Offer Marketing Illustration

Product benefits / Features

Network Management Cards

Benefits



Monitoring and alarming

Stay informed with real-time monitoring and instant alerts to quickly address issues before they impact operations.



Preventative management

Proactively manage systems to prevent failures and reduce downtime through early detection and action.



Ongoing security compliance

Ensure continuous adherence to security standards and protocols to protect against evolving threats.



Image of product / Alternate images

Alternative

