

Product datasheet

Specifications



Easy UPS 3S 10 kVA 400 V 3:3 UPS for internal batteries

Local distributor code:

422503538

E3SUPS10KHB

Overview

Presentation

High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 10 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is for internal batteries, but is supplied without batteries, so you can easily customize the battery runtime. For battery runtime details, see the runtime charts published under the Documents tab.

Main

Main input voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Other input voltage	380 V 415 V
Maximum input current	18 A
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.9 leading to 0.9 lagging
Cos phi	0.99
Efficiency at full load	304...477 V
Input frequency	45...65 Hz
Output voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Other output voltage	380 V 415 V
Rated power in W	10 kW
Rated power in VA	10 kVA
Harmonic distortion	Less than 3 %
Maximum configurable power in VA	10 kVA
Maximum configurable power in W	10 kW
Output harmonic distortion	< 3% linear load
Output overload operation	130-150% for 1 minute and 125-130% for 10 minutes
Output voltage tolerance	+/- 1.5 %
UPS topology	Double conversion online
Output frequency	50 Hz sync to mains 60 Hz sync to mains

Complementary

Maximum short-circuit current	10 kA
Battery type	Lead-acid internal
UPS connectivity	Optional network management card 3
Color	White (RAL 9003)
Height	140 cm
Width	38 cm
Depth	92.8 cm
Product weight	112 kg
USB compatible	Yes
Provided equipment	Dust filter Installation guide
Range of product	Easy UPS 3S
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CE EAC RCM
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...15240 m
IP protection	IP20
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	60 dBA
Heat dissipation	516 W
Operating altitude	0...3333 ft

Batteries & Runtime

Battery type	VRLA
Battery voltage	240 V
Included battery module	0
Empty battery slot	3
Discharge battery voltage	+/- 198 V DC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	164.000 cm
Package 1 Width	56.300 cm
Package 1 Length	101.400 cm
Package 1 Weight	144.990 kg

Logistical informations

Country of origin CN

Contractual warranty

Warranty (in months) 12



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	14 741 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 398 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	28 kg CO2 eq.
Carbon footprint of the installation phase [A5]	28 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	12 959 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	327 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	Dc6af940-cee3-4c52-a4a7-fc487db91a72
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	82
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

