

# Product datasheet

Specifications



## Easy UPS battery module, 24V DC-DC, DIN Rail, Industrial, 4.5Ah

XB005XPDR

EAN Code: 0731304451518

### Main

Main Input Voltage	24 V DC
Product or component type	Battery accessory
Main Output Voltage	24 V DC
Battery type	VRLA
Provided equipment	User manual

### Batteries & Runtime

Battery location	Battery cabinet
Device mounting	DIN rail
Battery voltage	24 V

### Physical

Colour	Metal grey
Height	129 mm
Width	192 mm
Depth	119 mm
Product weight	4.5 kg
Mounting preference	No preference
USB compatible	No

### Output

Battery capacity	4.5 Ah
------------------	--------

### Conformance

Standards	IEC 62368-1
Product certifications	CE TÜV

### Environmental

Ambient air temperature for operation	-15...50 °C
Operating altitude	0...3000 m
Relative humidity	0...95 %
Ambient air temperature for storage	-15...70 °C

---

Storage altitude	0...3000 m
Storage Relative Humidity	0...95 %

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.470 cm
Package 1 Width	19.000 cm
Package 1 Length	18.800 cm
Package 1 Weight	4.800 kg
Unit Type of Package 2	P12
Number of Units in Package 2	8
Package 2 Height	45.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	53.928 kg

---

## Logistical informations

---

Country of origin	CN
-------------------	----

---

## Contractual warranty

---

Warranty (in months)	12
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	22 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	18 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	17 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

