



DATA SHEET

# PICS150-01000 LOC Prime

picoScan100  
2D LiDAR sensors

# SICK

Sensor Intelligence

## 2D LIDAR SENSORS

# PICS150-01000 LOC Prime

## ORDERING INFORMATION

Type	part no.
PICS150-01000 LOC Prime	<a href="#">1141396</a>

Further device versions and accessories at [www.sick.com/picoScan100](http://www.sick.com/picoScan100)



## DETAILED TECHNICAL DATA

## FEATURES

Application	Indoor, Outdoor	
Description	picoScan150 incl. software for contour- and code-based position determination of mobile platforms and incl. Virtual Line Navigation	
Variant	Standard (not pre-configured)	
Measurement principle	HDDM <sup>1)</sup>	
Light source	Infrared (905 nm)	
Laser class	1 (IEC 60825-1:2014, EN 60825-1:2014+A11:2021)	
Aperture angle	Horizontal	276°
Scanning frequency	15 Hz 20 Hz 25 Hz Depends on the Dynamic Sensing Profile <sup>1)</sup>	
Angular resolution	Horizontal	0.1°, At 20 Hz 0.25°, At 40 Hz
Scan field flatness	± 1°	
Working range	0.05 m ... 60 m <sup>1)</sup>	
Blind zone	0 m ... 0.05 m	
Scanning range	At 90% remission factor and 10 klx 51 m At 10% remission factor and 10 klx 25 m	
Spot size	Divergence, typ.: 4.8 mrad On the optics cover: 8 mm	

<sup>1)</sup> For details, see the working range diagram in the technical drawings section.

Amount of evaluated echoes	3
----------------------------	---

<sup>1)</sup> For details, see the working range diagram in the technical drawings section.

## MECHANICS/ELECTRONICS

Connection type	1 x "Ethernet" connection, 4-pin M12 female connector, D-coded 1 x "POWER" connection, 12-pin M12 plug, A-coded
System plug	See system plug 2130754, Assembled to the rear
Supply voltage	9 V DC ... 30 V DC
Power consumption	Typ. 4.5 W, max. 17 W with loaded digital outputs, see system plug 2130754
Output current	≤ 200 mA
Housing material	Aluminum with Suretec650 coating
Housing color	Anthracite gray (RAL 7016)
Optical hood	Polycarbonate, scratch-resistant coating
Enclosure rating	IP65 (IEC 60529:1989+AMD1:1999+AMD2:2013) <sup>1)</sup> IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013) <sup>1)</sup>
Protection class	III (IEC 61140:2016-11)
Electrical safety	IEC 61010-1:2010-06+AMD1:2016
Weight	220 g, without system plug
Dimensions (L x W x H)	60 mm x 60 mm x 82 mm
Ventilation element	Yes
MTBF	> 100 years
MTTFd	> 100 years (at 25 °C ambient temperature), EN ISO 13849-1:2015

<sup>1)</sup> With system plug connected.

## SAFETY-RELATED PARAMETERS

MTTF <sub>0</sub>	> 100 years, at 25 °C ambient temperature (EN ISO 13849-1:2015)
-------------------	---

## FUNCTIONS

Digital add-ons	Dynamic Sensing Profile package Multi-echo technology Data Reduction & Data Preparation package Reliability package LMDscandata (data format) Reflector detection IMU (Inertial Measurement Unit)
-----------------	---

## PERFORMANCE

Output data LiDAR-LOC	Position (x, y, direction angle)
Speed LiDAR-LOC	≤ 3 m/s, translatory ≤ 90 °/s, rotatory
Localization accuracy	Typ. < 10 mm, position Typ. < 0.25°, orientation
Beam deviation	Typ. 0.27°   4.8 mrad
Data output per scan segment	Segment size 30° at ≤ 25 Hz, Segment size 60° at ≥ 30 Hz
Scan/frame rate	44,161 measurement point/s ... 165,603 measurement point/s, Depends on the Dynamic Sensing Profile and number of echoes
Latency of the measurement data output	Segment size 30° at < 25 Hz: ≤ 10 ms (3 σ) Segment size 60° at ≥ 30 Hz: ≤ 15 ms (3 σ), Depends on the Dynamic Sensing Profile and number of echoes

<sup>1)</sup> Typical value; real value depends on ambient conditions and the selected Dynamic Sensing Profile.

<sup>2)</sup> 10 ktx and 100 ktx; 1 σ.

## 2D LIDAR SENSORS - PICS150-01000 LOC PRIME

Detectable object shape	Almost any
Systematic error	Typ. $\pm 20$ mm <sup>1)</sup> Max. $\pm 30$ mm
Statistical error	$\leq 5$ mm (0.05 m ... 5 m) <sup>2)</sup>
Integrated application	2D Object Detection LiDAR-LOC 2 Virtual Line Navigation CODE-LOC Output of measurement data

<sup>1)</sup> Typical value; real value depends on ambient conditions and the selected Dynamic Sensing Profile.

<sup>2)</sup> 10 klx and 100 klx; 1 o.

### INTERFACES

Ethernet	Function	✓, UDP/IP (Compact, MSGPACK), TCP/IP (LMDscandata)
	Data transmission rate	Data interface (read result output), OPC DA, NTP, Measured data output (distance, RSSI) 10 Mbit/s ... 100 Mbit/s, half/full-duplex
Digital inputs/outputs		6, customizable, see system plug 2130754
Output data		Position (x, y, direction angle)
Optical indicators		2 LEDs
Configuration software		SOPASair (web browser) SOPAS ET (software) REST API
Driver		ROS1, ROS2, C++, Python

### AMBIENT DATA

Remission factor		1.8 % ... > 1,000 % (Reflector)
Electromagnetic compatibility (EMC)	Emitted radiation	Industrial environment (IEC 61000-6-4:2018 / EN IEC 61000-6-4:2019 / IEC 61000-6-4:2006+A1:2010 / EN 61000-6-4:2007+A1:2011)
	Emitted radiation	Business and commercial areas as well as small enterprises (IEC 61000-6-8:2020 / EN IEC 61000-6-8:2020)
	Electromagnetic immunity	Industrial environment (IEC 61000-6-2:2016 / EN IEC 61000-6-2:2019 / IEC 61000-6-2:2005 / EN 61000-6-2:2005 / EN 61000-6-2:2005/AC:2005)
	Application areas	Automotive (UN ECE R10) <sup>1)</sup>
	Application areas	Agricultural and forestry machinery (ISO 14982-1, ISO 14982-2) <sup>1) 2)</sup>
	Application areas	Earthmoving and construction machinery (ISO 13766-1) <sup>1) 2)</sup>
Vibration resistance	Sine resonance scan	10 Hz ... 1,000 Hz, 1 g <sup>3)</sup>
	Sine test	10 Hz ... 500 Hz, 10 g, 10 frequency cycles <sup>3)</sup>
	Noise test	10 Hz ... 500 Hz, 13.5 g RMS, 5 h <sup>4)</sup> Short restriction in measurement data availability possible during peak loads.
Shock resistance		100 g, 6 ms, $\pm 3$ single shocks/axis <sup>5)</sup> 40 g, 6 ms, $\pm 4,000$ continuous shocks/axis <sup>5)</sup> 50 g, 3 ms, $\pm 5,000$ continuous shocks/axis <sup>5)</sup> Short restriction in measurement data availability possible.
Ambient operating temperature		$-33$ °C ... $+50$ °C
Storage temperature		$-40$ °C ... $+70$ °C

<sup>1)</sup> Load dump: from ISO 16750-2 Test B Severity Level 4 passed for 12 V systems. Required in case of transient disturbances on the input filtering signal lines (debounce > 10 ms).

<sup>2)</sup> The requirements of ISO 13766-1 and DIN EN ISO 14982-1 for immunity to electrostatic discharge (ESD) are only met in areas that can be easily touched from the outside.

<sup>3)</sup> IEC 60068-2-6:2007.

<sup>4)</sup> IEC 60068-2-64:2008.

<sup>5)</sup> IEC 60068-2-27:2008.

<sup>6)</sup> EN 60068-2-14:2009.

Temperature change		-33 °C ... +50 °C, 10 cycles <sup>6)</sup>
Damp heat	Cyclical	+ 25 °C ... + 55 °C, 95 % RH, non-condensing (operation/storage/transport) (EN 60068-2-30)
	Static	+ 40 °C ... +93 °C, non-condensing (operation) (EN 60068-2-78)
Relative humidity	Operation	< 80 %, Non-condensing (EN 60068-2-30:2005)
	Storage	≤ 90 %, Non-condensing (EN 60068-2-30:2005)
Ambient light immunity		100 klx, indirect
Altitude (above sea level)		< 5,000 m

<sup>1)</sup> Load dump: from ISO 16750-2 Test B Severity Level 4 passed for 12 V systems. Required in case of transient disturbances on the input filtering signal lines (debounce > 10 ms).

<sup>2)</sup> The requirements of ISO 13766-1 and DIN EN ISO 14982-1 for immunity to electrostatic discharge (ESD) are only met in areas that can be easily touched from the outside.

<sup>3)</sup> IEC 60068-2-6:2007.

<sup>4)</sup> IEC 60068-2-64:2008.

<sup>5)</sup> IEC 60068-2-27:2008.

<sup>6)</sup> EN 60068-2-14:2009.


## GENERAL NOTES

Note on use	The sensor does not constitute a safety component as defined by relevant legislation on machine safety.
-------------	---

## CERTIFICATES

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
China RoHS	✓
cTUVus certificate	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓


**DIMENSIONAL DRAWING**



Dimensions in mm (inch)

- ① M4 threaded mounting hole; 4.2 mm deep; tightening torque 2.5 nm
- ② Tightening torque 2.5 nm, screw included in plug unit
- ③ Sending area
- ④ Transmission axis
- ⑤ Support point
- ⑥ M4 threaded mounting hole; 5.4 mm deep, tightening torque 2.5 nm
- ⑦ Area in which no reflective surfaces are allowed for mounted devices

**WORKING RANGE DIAGRAM WORKING RANGE FOR PICOSCAN150 PRIME-1**



All specified working range values apply to the “Standard” sensitivity mode

Dynamic Sensing Profile		Minimum		Typical				On high reflective targets and reflectors
		100 klx		10 klx		100 klx		
		10 %	90 %	10 %	90 %	10 %	90 %	
<b>15 Hz &amp; 0.33°</b>	Included in Prime	-	-	34 m	51 m	23 m	44 m	60 m
<b>15 Hz &amp; 0.5°</b>	Optional	-	-	34 m	51 m	23 m	44 m	60 m
<b>15 Hz &amp; 1°</b>	Included in Prime	-	-	34 m	51 m	23 m	44 m	60 m
<b>20 Hz &amp; 0.1°</b>	Included in Prime	14 m	27 m	23 m	38 m	16 m	31 m	45 m
<b>20 Hz &amp; 0.25°</b>	Optional	-	-	29 m	51 m	20 m	38 m	60 m
<b>25 Hz &amp; 0.25°</b>	Optional	17 m	33 m	28 m	51 m	19 m	36 m	60 m
<b>30 Hz &amp; 0.1°</b>	Optional	-	-	21 m	26 m	15 m	26 m	30 m
<b>40 Hz &amp; 0.25°</b>	Included in Prime	15 m	29 m	25 m	47 m	17 m	32 m	60 m
<b>50 Hz &amp; 0.25°</b>	Optional	-	-	23 m	44 m	16 m	31 m	55 m
<b>15 Hz &amp; 0.05°</b>	Optional	-	-	21 m	21 m	15 m	21 m	25 m
<b>40 Hz &amp; 0.125°</b>	Optional	-	-	21 m	26 m	14 m	26 m	30 m

Further information as well as suitable accessories, example applications and downloads such as CAD dimensional models, operating instructions and software can be found at [www.sick.com/1141396](http://www.sick.com/1141396)



SICK AG  
WALDKIRCH  
GERMANY  
SICK.COM

# SICK AT A GLANCE

SICK is a leading global technology company for intelligent sensors and integrated solutions in industrial automation. Our technologies set benchmarks, making your industrial processes more efficient, safer and more sustainable – both in logistics and manufacturing operations.

SICK combines sensor intelligence with industry expertise and certified consulting services. We provide the ideal foundation for scalable as well as tailor-made automation solutions and create added value along the entire value chain. Our close partnerships with our customers are more than just a promise: Together, we optimize productivity, improve quality, protect health and safety, and help build a sustainable future. All with empathy and trust.

Since 1946, we have been developing innovative technologies with passion and a pioneering spirit. With a global network in around 40 countries, SICK has a global presence and is always close by. The company's headquarters are located in Waldkirch near Freiburg, Germany. Our customers benefit from our understanding of both local and global requirements, which enables us to deliver tailor-made solutions

**SICK**  
Sensor Intelligence