

SIMATIC IPC847E (Rack PC, 19", 4HU); 3x Gbit Ethernet (IE/PN), RJ45; 1x DVI-D; 2x display ports; 1x COM 1; audio, 4x USB 3.1, 2x USB 3.1 (Type C) on the rear side; 2x USB 3.0 on the front; 1x USB 3.1 internal, temperature and fan monitoring; Watchdog, card retainer Xeon E-2278GE (8C/16T, 3.3 (4.7) GHz, 16 MB cache, TB, VT-d, AMT); board 11 slots: 3x PCI, 1x PCIe x16 (8 L), 5x PCIe x16 (4 L), 2x PCIe x4 (4 L); RAID1, 2x 2 TB HDD (Enterprise) 3.5" SATA; Enclosure with drive support Type B (for internal installation/ 0.5 g vibration, 5 g shock); 2x 100/240V AC redundant industrial power supply unit; 32 GB DDR4 SDRAM (2x 16 GB), Dual Channel; Without extension (HW); without operating system; Without expansions; Without power supply cable

| General information | |
|--|---|
| Product type designation | IPC847E |
| Installation type/mounting | |
| Mounting | For horizontal and vertical installation; prepared for telescopic rails; 19" mounting bracket can be removed externally; tower kit (optional) |
| Design | Rack PC, 19", 4U |
| Supply voltage | |
| Type of supply voltage | 100/240 V AC (autorange) 50 / 60 Hz; optional redundant 100/240 V AC |
| Line frequency | |
| <ul style="list-style-type: none"> Rated value 50 Hz Rated value 60 Hz | Yes Yes |
| Mains buffering | |
| <ul style="list-style-type: none"> Mains/voltage failure stored energy time | 20 ms |
| Processor | |
| Processor type | Intel Xeon E-2278GE (8C/16T, 3.3 (4.7) GHz, 16 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Xeon E-2176G (6C/12T, 3.7 (4.7) GHz, 12 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Core i7-8700 (6C/12T, 3.2 (4.6) GHz, 12 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Core i5-8500 (6C/6T, 3.0 (4.1) GHz, 9 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Core i3-8100 (4C/4T, 3.6 GHz, 6 MB Cache, VT-x/-d-Technology) |
| Chipset | Intel C246 |
| Graphic | |
| Graphics controller | Onboard Intel UHD graphics P630/630 integrated in processor; graphics card NVIDIA Quadro P400 PCIe (x16) triple head (optional) |
| Drives | |
| Hard disk | 1x 1 TB 3.5" SATA HDD, 2x 1 TB 3.5" SATA HDD, RAID1 2x 1 TB 3.5" SATA HDD, RAID1 2x 1 TB 3.5" SATA HDD (Enterprise), RAID1 2x 2 TB 3.5" SATA HDD (Enterprise), RAID1 2x 2 TB 3.5" SATA HDD (Enterprise) + 2 TB 3.5" SATA HDD (Enterprise) as hot spare, RAID5 3x 2 TB 3.5" SATA HDD (Enterprise), RAID5 3x 2 TB 3.5" SATA HDD (Enterprise) + 2 TB 3.5" SATA HDD (Enterprise) as hot spare, RAID1 2x 2 TB 3.5" SAS HDD (Enterprise) with PCIe x8 RAID controller incl. ZMCP module, RAID5 3x 2 TB 3.5" SAS HDD (Enterprise) with PCIe x8 RAID controller incl. ZMCP module |
| SSD | Yes; 1x 480 GB 2.5" SATA SSD, 1x 960 GB 2.5" SATA SSD, 2x 480 GB 2.5" SATA SSD, RAID1 2x 480 GB 2.5" SATA SSD; 1x 512 GB M.2 NVMe SSD, 1x 1 024 GB M.2 NVMe SSD |
| Slot for drives | Mounting internally in vibration/shock-absorbing drive cage Type B or mounting on the front in removable trays (hot swap in RAID configurations) in drive cage Type A; mounting internally on the fixed drive cage optional |
| Storage | |
| Main memory | 4 GB to 128 GB DDR4 2666 SDRAM DIMM, ECC optional |
| Capacity of main memory, max. | 128 Gbyte |
| Interfaces | |
| Interfaces/bus type | 1x COM1, 1x COM2 (optional), 2x DisplayPort, 1x DVI-D, audio (microphone in, line in, line out), 9x USB, 3x Gigabit Ethernet |
| serial interface | COM1: 1x RS 232, COM2 (optional): 1x RS 232 |
| Video interfaces | |
| <ul style="list-style-type: none"> Graphics interface | 2x DisplayPort and 1x DVI-D onboard; 1x VGA via DP-VGA adapter cable |

(optional); graphics card PCIe (x16), Triple Head (3x mini DisplayPort, 2 GB graphics memory, 3x mini DisplayPort to DisplayPort adapter cable) (optional)

| | |
|--|--|
| Industrial Ethernet | |
| <ul style="list-style-type: none"> • Industrial Ethernet interface <ul style="list-style-type: none"> — 100 Mbps — 1000 Mbps | <p>Yes</p> <p>Yes</p> |
| Interrupts/diagnostics/status information | |
| LED status display | POWER, HDD, ETHERNET 1, ETHERNET 2, ETHERNET 3, WATCHDOG, TEMP, FAN, HDD3 ALARM, HDD2 ALARM, HDD1 ALARM, HDD0 ALARM |
| Integrated Functions | |
| Monitoring functions | |
| <ul style="list-style-type: none"> • Temperature monitoring • Fan • Monitoring function via network | <p>Yes</p> <p>Yes</p> <p>Optional</p> |
| Degree and class of protection | |
| IP (at the front) | IP41 |
| IP (rear) | IP20 |
| Standards, approvals, certificates | |
| CE mark | Yes; For use in industrial areas as well as domestic, business and commercial environments (emitted interference: EN 61000-6-3:2007 +A1:2011, noise immunity: EN 61000-6-2:2005) |
| CSA approval | Yes; CAN/CSA-C22.2 No. 61010-2-201 Second Edition |
| UL approval | Yes; UL 61010-2-201 Second Edition, File E85972 |
| cULus | Yes; UL 61010-2-201 Second Edition; CAN/CSA-C22.2 No. 61010-2-201 Second Edition |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| Dust protection | With front door closed: G2 EN 779, 99% of particles > 0.5 mm are filtered |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • min. • max. | <p>0 °C; Max. 10 °C/h (no condensation)</p> <p>50 °C</p> |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> • min. • max. | <p>-20 °C; Max. 20 °C/h (no condensation)</p> <p>60 °C</p> |
| Vibrations | |
| <ul style="list-style-type: none"> • Vibration resistance during operation acc. to IEC 60068-2-6 | Tested according to IEC 60068-2-6: 10 cycles, 10 Hz to 58 Hz: 0.0375 mm, 58 Hz to 500 Hz: 4.9 m/s ² (0.5 g) |
| Operating systems | |
| pre-installed operating system | Windows 10 Enterprise 2016 LTSB, multi-language (64-bit); Windows 10 IoT Enterprise 2019 LTSC, multi-language (64-bit); Windows Server 2016 Standard Edition incl. 5 multi-language clients (64-bit); Windows Server 2019 Standard Edition incl. 5 multi-language clients (64-bit) |
| without operating system | Yes |
| Dimensions | |
| Width | 430 mm |
| Height | 177 mm; 4U |
| Depth | 444 mm |
| Approvals / Certificates | |
| General Product Approval | |



[Manufacturer Declaration](#)



[Miscellaneous](#)

General Product Approval



[BIS CRS](#)



| EMV | Dangerous goods | Environment | |
|-----|-----------------|-------------|--|
|-----|-----------------|-------------|--|



[Dangerous goods information](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

last modified:

3/1/2026